

INDUSTRIAL COMPONENT DATA

2CSF202002R1630 ABB FH202 AC-63/0,03 Resid. Current Dev.

Brand: ABB | Manufacturer Part Number: 2CSF202002R1630



Manufacturer	ABB
MPN / Reference	2CSF202002R1630
Catalog number	202002
Category	Residual current circuit breaker (RCCB)
Minimum order	1 Pcs
Document ID	EO-4E47835208
Generated	2026-07-31

Product Overview

FH202 AC-63/0,03 - Resid. Current Dev.

Int.dif.FH202AC-63/0.03 2p 63A AC 30mA

Residual Current Circuit Breaker FH200 - 2P - 30 mA - 63 A - Type AC

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path ABB > Residential / Tertiary > FH200

Additional Product Information

ABB EcoSolutions

ABB EcoSolutions Yes

EcoSolutions Profile 9AKK108470A4863

Recyclability Rate of the Product acc. to EN45555 Design for Closing Resource Loops - Standard EN45555 - 72.34 %

ABB Site Meeting Group Waste To Landfill Target No non-hazardous waste is sent to a landfill

UL 2799 Zero Waste To Landfill Validation available

Sustainable Material Content in Packaging (wt. %) Recycled Paper - 0 %

Recycled Cardboard - 19.59 %

Recycled Cardboard - 78.37 %

Extended Product Lifetime Product Durability

Offered with Takeback Services Take Back for Recycling

End Of Life Disassembling Instructions 9AKK108469A2269

Environmental Product Declaration - EPD 9AKK108469A6622

Technical

Type of Residual Current Type AC
Rated Service Short-Circuit Breaking Capacity (Ics) 6 kA
Maximum Surge Current 0.25 kA
Leakage Current Type AC
Electrical Endurance 10000 cycle
Mechanical Endurance 20000 cycle
Number of Poles 2P
Number of Modular Spacings per DIN Rail 2
Operating Characteristic Instantaneous
Options Provided None
Accessories Available No
Rated Cross-Section 4 - Multi-Wired 10 ... 25 mm²
1 - Solid-Core 25 ... 25 mm²
Electrical
Short-Circuit Current Rating (SCCR) 0.03 A
Rated Voltage (Ur) 230 V
Rated Operational Voltage acc. to IEC 60898-1 230 V
Rated Insulation Voltage (Ui) acc. to IEC/EN 60664-1 500 V
Rated Impulse Withstand Voltage (Uimp) 4 kV
Input Voltage Type AC
Rated Current (In) 63 A
Rated Residual Current 30 mA
Rated Conditional Short-Circuit Current (Inc) 6 kA
Rated Frequency (f)....

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send ABB / 2CSF202002R1630 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.