

INDUSTRIAL COMPONENT DATA

2CSF204003R3400 ABB FH204 AC-40/0,3 Residual Current Dev.

Brand: ABB | Manufacturer Part Number: 2CSF204003R3400



Manufacturer	ABB
MPN / Reference	2CSF204003R3400
Catalog number	204003
Category	Residual current circuit breaker (RCCB)
Minimum order	1 Pcs
Document ID	EO-9A2BDFB028
Generated	2026-08-01

Product Overview

FH204 AC-40/0,3 - Residual Current Dev.

Int.dif.FH204AC-40/0.3 4p 40A AC 300mA

Residual Current Circuit Breaker FH200 - 4P - 300 mA - 40 A - Type AC

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path ABB > Residential / Tertiary > FH200

Additional Product Information

ABB EcoSolutions

ABB EcoSolutions Yes

EcoSolutions Profile 9AKK108470A4863

Recyclability Rate of the Product acc. to EN45555 Design for Closing Resource Loops - Standard EN45555 - 72.34 %

ABB Site Meeting Group Waste To Landfill Target No non-hazardous waste is sent to a landfill

UL 2799 Zero Waste To Landfill Validation available

Sustainable Material Content in Packaging (wt. %) Recycled Paper - 0 %

Recycled Cardboard - 19.59 %

Recycled Cardboard - 78.37 %

Extended Product Lifetime Product Durability

Offered with Takeback Services Take Back for Recycling

End Of Life Disassembling Instructions 9AKK108469A2269

Environmental Product Declaration - EPD 9AKK108469A6622

Technical

Type of Residual Current Type AC

Rated Service Short-Circuit Breaking Capacity (Ics) 6 kA

Maximum Surge Current 0.25 kA

Leakage Current Type AC

Electrical Endurance 10000 cycle

Mechanical Endurance 20000 cycle

Number of Poles 4P

Number of Modular Spacings per DIN Rail 4

Operating Characteristic Instantaneous

Position of Neutral Terminals Right

Options Provided None

Accessories Available No

Rated Cross-Section 4 - Multi-Wired 10 ... 25 mm²1 - Solid-Core 25 ... 25 mm²**Electrical**

Short-Circuit Current Rating (SCCR) 0.3 A

Rated Voltage (Ur) 230/400 V

Rated Operational Voltage acc. to IEC 60898-1 400 V

Rated Insulation Voltage (Ui) acc. to IEC/EN 60664-1 500 V

Rated Impulse Withstand Voltage (Uimp) 4 kV

Input Voltage Type AC

Rated Current (In) 40 A

Rated Residual Current 300 mA

Rated Conditional Short-Circuit...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send ABB / 2CSF204003R3400 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.