

INDUSTRIAL COMPONENT DATA

2CSF204004R1630 ABB FH204 AC-63/0,03 Residual Current Dev.

Brand: ABB | Manufacturer Part Number: 2CSF204004R1630



Manufacturer	ABB
MPN / Reference	2CSF204004R1630
Catalog number	204004
Category	Residual current circuit breaker (RCCB)
Minimum order	1 Pcs
Document ID	EO-7E0541BDA2
Generated	2026-08-01

Product Overview

FH204 AC-63/0,03 - Residual Current Dev.

Int.dif.FH204AC-63/0.03 4p 63A AC 30mA

Residual Current Circuit Breaker FH200 - 4P - 30 mA - 63 A - Type AC

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path ABB > Residential / Tertiary > FH200

Additional Product Information

The RCCBs FH200 series assures protection to people and installations against fault current to earth. A large offer for standard instantaneous AC and A types is particularly suitable for installation in domestic applications.

Ordering

EAN:8012542894100

Minimum Order Quantity:1 piece

Customs Tariff Number:85363030

Dimensions

Product Net Width:0.070m

Product Net Height:0.085m

Product Net Depth:0.069m

Product Net Weight:0.360kg

Container Information

Package Level 1 Units:1 piece

Package Level 1 Width:0.082 m
Package Level 1 Height:0.078 m
Package Level 1 Length:0.096 m
Package Level 1 Gross Weight:0.403 kg
Package Level 1 EAN:8012542894100
Technical
Standards:IEC 61008
Operating Characteristic:Instantaneous
Type of Residual Current:AC type
Rated Residual Current:30 mA
Rated Current (In):63 A
Number of Poles:4
Position of Neutral Terminals:Right
Power Loss:at Rated Operating Conditions per Pole 4.4 W
Certificates and Declarations (Document Number)
Declaration of Conformity - CE:ITSCE116F200
Classifications
Object Classification Code:Q
ETIM 4:EC000003 - Residual current circuit breaker (RCCB)
ETIM 5:EC000003 - Residual current circuit breaker (RCCB)
ETIM for 2CSF204004R1630 Circuit breakers and fuses (EC000003)
Feature Name
Feature Value
Number of poles (EF001391)
4
Rated voltage (EF000228)
400 V
Rated current (EF000227)
63 A
Rated insulation voltage Ui (EF001366)
500 V
Rated impulse withstand voltage Uimp (EF011980)
4 kV
Mounting method (EF000003)
DIN rail
Leakage current type (...)

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send ABB / 2CSF204004R1630 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.