

INDUSTRIAL COMPONENT DATA

2CCL562310E1324 ABB FS401MK-C32/0.03

Brand: ABB | Manufacturer Part Number: 2CCL562310E1324



Manufacturer	ABB
MPN / Reference	2CCL562310E1324
Catalog number	562310
Category	Earth leakage circuit breaker
Minimum order	1 Pcs
Document ID	EO-C9B5B61B5F
Generated	2026-08-04

Product Overview

FS401MK-C32/0.03

SMISSLINE-I.Com FS401MK C 32A 30mA

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	ABB > Industrial
--------------	------------------

Additional Product Information

ABB EcoSolutions

EcoSolutions Profile 9AKK108470A5866

Technical

Type of Residual Current Type F

Dielectric Test Voltage 2500 kV

Rated Ultimate Short-Circuit Breaking Capacity (Icu) 15 kA

Rated Residual Breaking Capacity (I?m) 10000 A

Rated Service Short-Circuit Breaking Capacity (Ics) (240 V AC) 7.5 kA

Rated Service Short-Circuit Breaking Capacity, in % of Icu (Ics) 10 kA

Maximum Surge Current 3 kA

Contact Position Indication Red ON / Green OFF

Energy Limiting Class 3

Electrical Endurance 10000 cycle

Mechanical Endurance 10000 cycle

Number of Protected Poles 1

Number of Poles 2P
Operating Characteristic Instantaneous (APR High Immunity)
Position of Neutral Terminals Right
Tightening Torque 2.8 N·m
Actuator Type Toggle
Earthing Switch Type Short-Time Delayed
Screw Terminal Type Failsafe Bi-directional Cylinder-lift Terminal
Actuator Material Insulation Group II, Black, Sealable
Accessories Available Yes
Connecting Capacity Stranded 0.75 ... 35 mm²
Flexible 0.75 ... 25 mm²
Rated Cross-Section 1 - Solid-Core 0.75 ... 35 mm²
4 - Multi-Wired 0.75 ... 10 mm²
Electrical
Short-Circuit Current Rating (SCCR) 0.03 A
Tripping Characteristic C
Rated Operational Voltage acc. to IEC 60898-1 240 V
Rated Insulation Voltage (Ui) acc. to IEC/EN 60664-1 500 V
Rated Impulse Withstand Voltage (Uimp) 4 kV
Input Voltage Type AC
Rated Current (In) 32 A
Rated Residual Current 30 mA
Rated Short-Circuit Capacity 10 kA
Rated Frequency (f) 50 ... 60 Hz
Power Loss 5.6 W
Overvoltage Category III
Design
Housing M...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send ABB / 2CCL562310E1324 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.