

INDUSTRIAL COMPONENT DATA

1SFL647025R6911 ABB GAF1250-10-11 48-130V 50/60Hz / 48-130V DC Contactor

Brand: ABB | Manufacturer Part Number: 1SFL647025R6911



Manufacturer	ABB
MPN / Reference	1SFL647025R6911
Catalog number	647025
Category	Power contactor, DC switching
Minimum order	1 Pcs
Document ID	EO-A25B5C99B6
Generated	2026-08-05

Product Overview

GAF1250-10-11 48-130V 50/60Hz / 48-130V DC Contactor

GAF1250-10-11 CONT. 1P 1000VDC 48-130Vac

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	ABB > Contactors and overload relays > "A" SECRLP
--------------	---

Additional Product Information

Ordering

Minimum Order Quantity 1 piece

Customs Tariff Number 85364900

Popular Downloads

EPLAN Data 9AAC171154_EPLAN

Data Sheet, Technical Information 1SBC100214C0202

Data Sheet, Technical Information (Part 2) 1SAC200017M0002

Instructions and Manuals 1SFC101045M9701

CAD Dimensional Drawing 2CDC001079B0201

Dimensions

Product Net Width 210 mm

Product Net Depth / Length 242 mm

Product Net Height 344 mm

Product Net Weight 15 kg

Technical

Number of Main Contacts NO 1

Number of Main Contacts NC 0

Number of Auxiliary Contacts NO 1

Number of Auxiliary Contacts NC 1

Number of Poles 1P

Rated Operational Voltage Main Circuit 1000 V

Conventional Free-air Thermal Current (I_{th}) acc. to IEC 60947-4-1, Open Contactors ? = 40 °C 1260 ARated Operational Current DC-1 (I_e) (1000 V) 3 Poles in Series, 40 °C 1250 A

(1000 V) 3 Poles in Series, 55 °C 1040 A

(1000 V) 3 Poles in Series, 70 °C 875 A

(220 V) 3 Poles in Series, 40 °C 1250 A

(220 V) 3 Poles in Series, 55 °C 1040 A

(220 V) 3 Poles in Series, 70 °C 875 A

(400 V) 3 Poles in Series, 40 °C 1250 A

(400 V) 3 Poles in Series, 55 °C 1040 A

(400 V) 3 Poles in Series, 70 °C 875 A

(600 V) 3 Poles in Series, 40 °C 1250 A

(600 V) 3 Poles in Series, 55 °C 1040 A

(600 V) 3 Poles in Series, 70 °C 875 A

Rated Insulation Voltage (U_i) acc. to UL/CSA 1000 VRated Impulse Withstand Voltage (U_{imp}) Main Circuit 8 kV

Mechanical Durability 0.5 million

Maximum Mechanical Switching Frequency 300 cycles per hour

Coil Operating Limits (acc. to IEC 60947-4-1) 0.85 x....

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send ABB / 1SFL647025R6911 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.