


INDUSTRIAL COMPONENT DATA

2CCS864001R1427 ABB High Performance Circuit Breaker S800S Tripping characteristic K Number of poles 4 Rated..

Brand: ABB | Manufacturer Part Number: 2CCS864001R1427



Manufacturer	ABB
MPN / Reference	2CCS864001R1427
Catalog number	864001
Category	Miniature circuit breaker (MCB)
Minimum order	1 Pcs
Document ID	EO-475529B3CA
Generated	2026-08-05

Product Overview

High Performance Circuit Breaker - S800S - Tripping characteristic K - Number of poles 4 - Rated operational current 10A - Rated operational voltage 1000V DC
Int.aut. S804S-UCK10 4p 10A UCK 50kA
S804S-UCK10 High Performance MCB

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	ABB > Industrial > S800S-UC
--------------	-----------------------------

Additional Product Information

ABB EcoSolutions

ABB EcoSolutions Yes

EcoSolutions Profile 9AKK108471A1082

Recyclability Rate of the Product acc. to EN45555 Design for Closing Resource Loops - Standard EN45555 - 86.29 %

ABB Site Meeting Group Waste To Landfill Target No non-hazardous waste is sent to a landfill

End Of Life Disassembling Instructions 9AKK108470A2575

Environmental Product Declaration - EPD 9AKK108470A1695

9AKK108470A1696

Technical

Type of Residual Current Standard Version

Rated Ultimate Short-Circuit Breaking Capacity (Icu) (1000 V DC) 50 kA

Rated Service Short-Circuit Breaking Capacity (Ics) (1000 V DC) 50 kA

Contact Position Indication ON / OFF / TRIP

Energy Limiting Class 3

Number of Protected Poles 4

Number of Poles 4P

Release Type K

Actuator Marking I / O

Options Provided Universal current

Accessories Available Yes

Connecting Capacity Flexible 0 ... 50 mm²

Rigid 0 ... 70 mm²

Terminal Type Screw Terminals

Electrical

Tripping Characteristic UC-K

Rated Operational Voltage acc. to IEC 60947-2 1000 V DC

Rated Insulation Voltage (Ui) acc. to IEC/EN 60664-1 1500 V

Rated Impulse Withstand Voltage (Uimp) 8 kV

Input Voltage Type DC

Rated Current (In) 10 A

Frequency (f) 0...0 Hz

Rated Frequency (f) 0 Hz

Power Loss Total 6 W

at Rated Operating Conditions per Pole 1.5 W

Overvoltage Category III

Material Compliance

RoHS Declaration 2CCC005084D0202

RoHS Information Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019

RoHS Date 20211214

REACH Declaration 9AKK108470A9089

REACH Information....

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send ABB / 2CCS864001R1427 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.