

INDUSTRIAL COMPONENT DATA

2CDS211103R0204 ABB Int.aut. SH201-C20NA 1p+N 20A C 6kA

Brand: ABB | Manufacturer Part Number: 2CDS211103R0204



Manufacturer	ABB
MPN / Reference	2CDS211103R0204
Catalog number	211103
Category	Miniature circuit breaker (MCB)
Minimum order	1 Pcs
Document ID	EO-C44098A178
Generated	2026-08-05

Product Overview

Int.aut. SH201-C20NA 1p+N 20A C 6kA
 Miniature Circuit Breaker - SH200 - 1P+N - 20 A - C - (AC) 6 kA

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path **ABB > Residential / Tertiary > SH200**

Additional Product Information

ABB EcoSolutions
 ABB EcoSolutions Yes
 EcoSolutions Profile 9AKK108471A1003
 Recyclability Rate of the Product acc. to EN45555 Design for Closing Resource Loops - Standard EN45555 - 92.1 %
 ABB Site Meeting Group Waste To Landfill Target No non-hazardous waste is sent to a landfill
 Extended Product Lifetime Product Durability
 End Of Life Disassembling Instructions 9AKK108468A3121
 Environmental Product Declaration - EPD 9AKK108468A1580
 Technical
 Dielectric Test Voltage 50 / 60 Hz - 1 min 2 kV
 Power Supply Connection Arbitrary
 Contact Position Indication ON / OFF
 Energy Limiting Class 3
 Electrical Endurance 20000 AC cycle

Mechanical Endurance 20000 cycle
Number of Protected Poles 1
Number of Poles 1P+N
Position of Neutral Terminals Right
Tightening Torque 2 N·m
Actuator Type Toggle
Screw Terminal Type Cage Terminal
Actuator Marking I / O
Actuator Material Insulation Group II, Black, Sealable
Recommended Screw Driver Pozidriv 2
Accessories Available No
Connecting Capacity Conductor 25 / 25 mm²
Flexible with Ferrule 0.75 ... 16 mm²
Flexible 0.75 ... 16 mm²
Rigid 0.75 ... 25 mm²
Stranded 0.75 ... 25 mm²
Installation Size acc. to DIN 43880 1
Terminal Type Screw Terminals
Electrical
Tripping Characteristic C
Rated Operational Voltage acc. to IEC 60898-1 230 V
Operational Voltage Maximum (Incl. Tolerance) 253 V AC
Minimum 12 V AC
Rated Insulation Voltage (Ui) acc. to IEC/EN 60664-1 440 V
Rated Impulse Withstand Voltage (Uimp) 4 kV
at 2000 m 5 kV
at Sea Level 6.2 kV
Input Voltage Type A...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send ABB / 2CDS211103R0204 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.