

INDUSTRIAL COMPONENT DATA

2TLA020006R2100 ABB JSHD4-1 Top part

Brand: ABB | Manufacturer Part Number: 2TLA020006R2100



Manufacturer	ABB
MPN / Reference	2TLA020006R2100
Catalog number	020006
Category	Agreement switch
Minimum order	1 Pcs
Document ID	EO-0AF27C4C91
Generated	2026-08-01

Product Overview

JSHD4-1 Top part
JSHD4-1 Top Module
JSHD4-1 Three-position handheld device - Top part

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path ABB > Fences and rolling doors > Control devices

Additional Product Information

Ordering
Minimum Order Quantity 1 piece
Customs Tariff Number 8536909599
Product Main Type JSHD4
Product Name Three-position handheld device - Top part
Sub-Function No auxiliary button
Sub-Function 2 Holder for Eva (home position) with bottom part AL
Status Indicator No
Popular Downloads
Data Sheet, Technical Information 2TLC010001C0202
CAD Dimensional Drawing 2CDC001079B0201
Marketing Video 2TLC010018N0201
Installation
Instructions and Manuals 2TLC172072M0201

Wiring Diagram 2TLC010143D0201

Dimensions

Product Net Depth / Length 340 mm

Product Net Height 157 mm

Product Net Width 56 mm

Product Net Weight 0.139 kg

CAD Dimensional Drawing 2CDC001079B0201

Safety Information

Performance Level (PL) Up to e

B10d Value Operations to Bottom Position 968 000

Operations to Middle Position 2 million

Technical

Communication Interface Contacts

Connection Configuration Depends on bottom part

Maximum Switching Current Main Circuit 0.02 mA

Maximum Switching Voltage Main Circuit 30 V

Minimum Switching Capacity Main Circuit 8 mA, 10 VDC

Number of Contacts CO 1

Number of Contacts NC 0

Number of Contacts NO 1

Rated Operational Current DC-12 (Ie) (24 V) 0.02 A

Rated Operational Voltage 24 V DC

Technical Information Operating force: Approx. 15 N for three-position button (ON), Approx. 45 N for three-position button (OFF), Approx. 2.5 N for top/front pushbutton; Mechanical service life: 1 million cycles, top to middle position, 100 000 cycles, middle to bottom position, and top/front push button

Tec...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send ABB / 2TLA020006R2100 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.