

INDUSTRIAL COMPONENT DATA

2TLA019995R0400 ABB JSHD4-2-AD Enabling Switch

Brand: ABB | Manufacturer Part Number: 2TLA019995R0400



Manufacturer	ABB
MPN / Reference	2TLA019995R0400
Catalog number	019995
Category	Agreement switch
Minimum order	1 Pcs
Document ID	EO-D8B4BA4467
Generated	2026-07-29

Product Overview

JSHD4-2-AD Enabling Switch
 JSHD4-2-AD Ergonomic 3 pos.
 JSHD4-2-AD Three-position handheld device - Complete

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path ABB > Fences and rolling doors > Control devices

Additional Product Information

Ordering
 Minimum Order Quantity 1 piece
 Customs Tariff Number 8536909599
 Product Main Type JSHD4
 Product Name Three-position handheld device - Complete
 Function Three-position device used to allow a limited movement of the machine when the operator is in the dangerous area.
 Sub-Function 1 front and 1 top auxiliary buttons
 Status Indicator Yes
 Popular Downloads
 Data Sheet, Technical Information 2TLC010001C0202
 CAD Dimensional Drawing 2CDC001079B0201
 EPLAN Data 9AAC170170_EPLAN
 Marketing Video 2TLC010018N0201

Installation

Instructions and Manuals 2TLC172072M0201

Wiring Diagram 2TLC010143D0201

Dimensions

Product Net Depth / Length 60 mm

Product Net Height 200 mm

Product Net Width 34 mm

Product Net Weight 0.311 kg

CAD Dimensional Drawing 2CDC001079B0201

Safety Information

Performance Level (PL) Up to e

B10d Value Operations to Bottom Position 968 000

Operations to Middle Position 2 million

Technical

Communication Interface Contacts

Connection Configuration M12-8 male

Maximum Switching Current Main Circuit 0.02 mA

Maximum Switching Voltage Main Circuit 30 V

Minimum Switching Capacity Main Circuit 8 mA, 10 VDC

Number of Contacts CO 2

Number of Contacts NC 0

Number of Contacts NO 0

Rated Operational Current DC-12 (Ie) (24 V) 0.02 A

Rated Operational Voltage 24 V DC

Technical Information Operating force: Approx. 15 N for three-position button (ON), Approx. 45 N for three-position button (OFF), Approx. 2.5 N for top/front pushbutton; Mechanical service life: 1 million cycles, top to....

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send ABB / 2TLA019995R0400 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.