

INDUSTRIAL COMPONENT DATA

1SBV012113R1211 ABB LS35P13B11 Limit Switch

Brand: ABB | Manufacturer Part Number: 1SBV012113R1211



Manufacturer	ABB
MPN / Reference	1SBV012113R1211
Catalog number	012113
Category	End switch
Minimum order	1 Pcs
Document ID	EO-A36DBD54D6
Generated	2026-08-02

Product Overview

LS35P13B11 Limit Switch
Int.End.Carrera LS35P13B11

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path ABB > Detectors and limit switches > Limit FRCTL

Additional Product Information

Ordering

Minimum Order Quantity 1 piece
Customs Tariff Number 85364900

Popular Downloads

Data Sheet, Technical Information 1SBC141160C0201
Instructions and Manuals 1SBC141160C0201

Dimensions

Product Net Width 30 mm
Product Net Height 84 mm
Product Net Depth / Length 30 mm
Product Net Weight 0.064 kg

Technical

Action Type of the Contact Element (acc. to IEC 60947-5-1) Snap Action Contacts
Actuating Force Minimum Force acc. to IEC 60947-5-1 12 N
Actuation Speed acc. to IEC 60947-5-1 Max. 0.3 m/s

Actuator Type plastic roller plunger
Angular Head Adjustment adjustable head every 90°
Angular Lever Adjustment none
B10d Value Operations 30 Millions
Climatic Withstand according to IEC 68-2-3 and Salty Mist according to IEC 68-2-11
Conventional Free-air Thermal Current (Ith) acc. to IEC 60947-5-1, $\theta = 40\text{ °C}$ 10 A
Connecting Capacity Bar AWG 20 ... AWG 14 mm²
Bar 0.5 ... 2.5 mm²
Consistency (Measured over 1 Million Operations) 0.1 mm
Contact Element Form (acc. to IEC 60947-5-1) Zb
Connecting Terminals (delivered in open position) M3.5 (+,-) pozidriv 2 screw with cable clamp
Degree of Protection acc. to IEC 60529 IP65
Electrical Shock Protection acc. to IEC 536 Double insulation - Class II
Flammability According to UL94 V-0
Housing Material Plastic
Maximum Electrical Switching Frequency 3600 cycles per hour
(AC-15) 3600 cycles per hour
(DC-13) 3600 cycles per hour
Maximum Mounted Auxiliary Contacts 1 NO, 1 NC
Mechanical Durability 10 million
Mounting Type 30 mm (EN 50047)
Mounting by Sc...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send ABB / 1SBV012113R1211 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.