

INDUSTRIAL COMPONENT DATA

1SBV011641R1211 ABB LS43M41B11 Limit Switch

Brand: ABB | Manufacturer Part Number: 1SBV011641R1211



Manufacturer	ABB
MPN / Reference	1SBV011641R1211
Catalog number	011641
Category	End switch
Minimum order	1 Pcs
Document ID	EO-4A2FC28192
Generated	2026-07-29

Product Overview

LS43M41B11 Limit Switch

PA. C/ROL. PLA. DIA.18(22 P/LS4X)

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path ABB > Detectors and limit switches > Limit FRCTLP

Additional Product Information

Ordering

Minimum Order Quantity 1 piece

Customs Tariff Number 85364900

Popular Downloads

Data Sheet, Technical Information 1SBC141160C0201

Instructions and Manuals 1SBC141160C0201

Dimensions

Product Net Width 40 mm

Product Net Height 133 mm

Product Net Depth / Length 60 mm

Product Net Weight 0.279 kg

Technical

Action Type of the Contact Element (acc. to IEC 60947-5-1) Snap Action Simultaneous

Actuator Type plastic roller lever (Ø22 mm)

B10d Value Operations 50 Millions

Conventional Free-air Thermal Current (I_{th}) acc. to IEC 60947-5-1, $\theta = 40\text{ °C}$ 10 A
Degree of Protection acc. to IEC 60529 IP66
Housing Material Metal
Maximum Electrical Switching Frequency (AC-15) 3600 cycles per hour
(DC-13) 3600 cycles per hour
Maximum Mounted Auxiliary Contacts 1 NO, 1 NC
Mechanical Durability 25 million
Mounting Type 40 mm (EN 50041)
Number and Type of Bottom Cable Glands 1 x M20x1.5 - Bottom
Pilot Duty UL/CSA A600
Q600
Rated Impulse Withstand Voltage (U_{imp}) 6 kV
Rated Operational Current AC-15 (I_e) (230 V AC) 3.1 A
(400 V) NC 4
(24 V) 10 A
(130 V) 5.5 A
(240 V) 3 A
Rated Insulation Voltage (U_i) acc. to IEC 60947-5-1 and VDE 0110 (Gr. C) 500 V
acc. to UL/CSA 600 V
Rated Operational Current DC-13 (I_e) (24 V) 6 A
(110 V) 0.6 A
(125 V) 0.55 A
(250 V) 0.4 A
Short-Circuit Protective Devices gG Type Fuses 10 A
Environmental
Ambient Air Temperature Operation -25 ... +70 °C
Storage -30 ... +80 °C
Material Compliance
Conflict Minerals Reporting Template (CMRT) 9AKK108467A5658
REACH Declaration 1SBD2...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send ABB / 1SBV011641R1211 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.