

INDUSTRIAL COMPONENT DATA

1SBV013111R1211 ABB LS45M11B11 Limit Switch

Brand: ABB | Manufacturer Part Number: 1SBV013111R1211



Manufacturer	ABB
MPN / Reference	1SBV013111R1211
Catalog number	013111
Category	End switch
Minimum order	1 Pcs
Document ID	EO-BAC013DE90
Generated	2026-08-02

Product Overview

LS45M11B11 Limit Switch
Int.End.Carrera LS45M11B11

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path ABB > Detectors and limit switches > Limit FRCTLP

Additional Product Information

Ordering

Minimum Order Quantity 1 piece
Customs Tariff Number 85364900

Popular Downloads

Data Sheet, Technical Information 1SBC141160C0201
Instructions and Manuals 1SBC141160C0201

Dimensions

Product Net Width 40 mm
Product Net Height 107 mm
Product Net Depth / Length 44 mm
Product Net Weight 0.222 kg

Technical

Action Type of the Contact Element (acc. to IEC 60947-5-1) Snap Action Contacts
Actuating Force Minimum Force acc. to IEC 60947-5-1 22 N
Actuation Speed acc. to IEC 60947-5-1 Max. 0.5 m/s

Actuator Type stainless steel plain plunger
Angular Head Adjustment adjustable head every 90°
Angular Lever Adjustment none
B10d Value Operations 50 Millions
Climatic Withstand according to IEC 68-2-3 and Salty Mist according to IEC 68-2-11
Conventional Free-air Thermal Current (Ith) acc. to IEC 60947-5-1, $\theta = 40\text{ °C}$ 10 A
Connecting Capacity Bar AWG 20 ... AWG 14 mm²
Bar 0.5 ... 2.5 mm²
Consistency (Measured over 1 Million Operations) 0.05 mm
Contact Element Form (acc. to IEC 60947-5-1) Zb
Connecting Terminals (delivered in open position) M3.5 (+,-) pozidriv 2 screw with cable clamp
Degree of Protection acc. to IEC 60529 IP66
Electrical Shock Protection acc. to IEC 536 Class I
Housing Material Metal
Maximum Electrical Switching Frequency 3600 cycles per hour
(AC-15) 3600 cycles per hour
(DC-13) 3600 cycles per hour
Maximum Mounted Auxiliary Contacts 1 NO, 1 NC
Mechanical Durability 25 million
Mounting Type 40 mm (EN 50041)
Mounting by Screws (not supplied) 2 or 4 x M5 Screws
Movement t...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send ABB / 1SBV013111R1211 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.