

INDUSTRIAL COMPONENT DATA

LS60M41D11 1SBV011341R1411 ABB LS60M41D11 Limit Switch

Brand: ABB | Manufacturer Part Number: LS60M41D11



Manufacturer	ABB
MPN / Reference	LS60M41D11
Catalog number	1SBV011341R1411
Category	Position switch modular
Minimum order	1 Pcs
Document ID	EO-C9C692A30B
Generated	2026-07-29

Product Overview

LS60M41D11 Limit Switch

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	ABB > Detectors and limit switches > Limit FRCTLP
--------------	---

Additional Product Information

LS60M41D11 Limit Switch

Ordering

EAN:3471522005694

Minimum Order Quantity:10 piece

Customs Tariff Number:85369085

Dimensions

Product Net Width:60mm

Product Net Weight:0.300kg

Container Information

Package Level 1 Units:1 piece

Package Level 1 Width:135 mm

Package Level 1 Height:70 mm

Package Level 1 Length:65 mm

Package Level 1 Gross Weight:0.3 kg

Package Level 1 EAN:3471522005694

Environmental

Ambient Air Temperature: Operation -25 ... +70 °C

Storage -30 ... +80 °C

Resistance to Shock acc. to IEC 60068-2-27: Half-sine Pulse for 11 ms, No Change in Contact Position 50 m/s²

Resistance to Vibrations acc. to IEC 60068-2-6: 25g (10 to 500 Hz) no change in position of contacts greater than 100 µs

Technical UL/CSA

Pilot Duty of Contact Elements acc. UL508:A600

Q600

Additional Information

Action Type of the Contact Element (acc. to IEC 60947-5-1): non-overlapping slow action contacts

Actuation Speed: acc. to IEC 60947-5-1 Max. 1.50 m/s

acc. to IEC 60947-5-1 Min. 0.06 m/s

Actuation Torque: acc. to IEC 60947-5-1 Min. 0.15 N·m

Actuator Type: Ø22 mm polyamide roller lever

Angular Head Adjustment: adjustable head every 90°

Angular Lever Adjustment: 9° in 9°

Climatic Withstand: according to IEC 68-2-3 and salty mist according to IEC 68-2-11

Connecting Capacity: AWG 20 ... AWG 14

0.5 ... 2.5 mm²

Connecting terminals (delivered in open position): M3.5 (+, -) pozidriv 2 screw with cable clamp

Consistency (Measured over 1 Million Operations): 0.05 mm

Contact Element Form (acc. to IEC 60947-5-1): Zb

Conventional F...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEWSend ABB / LS60M41D11 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.**GLOBAL OFFICES**

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.