


## INDUSTRIAL COMPONENT DATA

# M3AA 63A 3GAA062311-ASF ABB Aluminum Engine for Process Industry 0.12 kW, 1500 rpm, 230/400 V, B3 mounting, ..

Brand: ABB | Manufacturer Part Number: M3AA 63 A



|                 |                                          |
|-----------------|------------------------------------------|
| Manufacturer    | ABB                                      |
| MPN / Reference | M3AA 63 A                                |
| Catalog number  | 3GAA062311-ASF                           |
| Category        | Cast iron M2BA and aluminium M3AA motors |
| Minimum order   | 1 unit                                   |
| Document ID     | EO-FD2B8EBB15                            |
| Generated       | 2026-08-05                               |

## Product Overview

M3AA 63A 3GAA062311-ASF ABB Aluminum Engine for Process Industry 0.12 kW, 1500 rpm, 230/400 V, B3 mounting, ..

## STRUCTURED PRODUCT DATA

## Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

## Classification & Catalog Path

Catalog path ABB &gt; Cast iron M2BA and aluminium M3AA motors &gt; IE2

## Additional Product Information

Product ID:3GAA062311-ASF

ABB Type Designation:M3AA 63A 4

Catalog Description:No Description Available

Additional Information

ABB Type Designation:M3AA 63A 4

Altitude:1000 m

Ambient Temperature:40 °C

Bearing:6201-2Z/C3

Bearing NDE:6201-2Z/C3

Country of Origin:China (CN)

Customs Tariff Number:85015100

Electrical Data:Conn Temp Class Freq Voltage Power Speed Current Power Factor Efficiency Torque IS/IN

Y -- 50 Hz 400 V 0.12 kW 1403 r/min 0.41 A 0.630 59.10 % 0.82 N·m 2.90

D -- 50 Hz 230 V 0.12 kW 1403 r/min 0.71 A 0.630 59.10 % 0.82 N·m 2.90

Y -- 60 Hz 460 V 0.12 kW 1724 r/min 0.38 A 0.600 64.00 % 0.66 N·m 3.30

Frame Material:Aluminum

Gross Weight:4.7kg

IC Class:IC411

IE Class Data (50 Hz):IE Class IE2

Full Load (100%) 59.1 %

Partial Load (75%) 55.8 %

Partial Load (50%) 47.1 %

IE Class Data (60 Hz):IE Class IE2

Full Load (100%) 64.0 %

Partial Load (75%) 59.7 %

Partial Load (50%) 51.0 %

IM Class:IMB3 IM1001

IP Rating:IP55

Insulation Class:ICLF

Made To Order:No

Minimum Order Quantity:1 piece

Number of Poles (High):4

Order Multiple:1 piece

Package Level 1 Units:0 carton

Product Name:3-Phase squirrel cage motor

Product Net Weight:3.7kg

Product Type:3AA2\_\_M3AA\_IE2\_AA

Quote Only:No

Replaced Product ID (OLD):3GAA062311-ASE

3GAA062001-ASC

3GVA062001-ASC

3GAA062311-ASC

3GAA062001-ASE

Selling Unit of Measure:piece

Stocked At (Warehouses):Menden, Germany

Sant Quirze del Vallés - BCN, Spain

Vittuone, Italy

Temperature Class Default:--

Terminator Box Location:D-End top

Two Speed Motor:No

T...

## REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send ABB / M3AA 63 A with the required quantity to [info@electricaonline.com](mailto:info@electricaonline.com) or use [electricaonline.com/request-quote](https://electricaonline.com/request-quote).

### GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.