

INDUSTRIAL COMPONENT DATA

M3JP 80MG 3GJP081370-ASK ABB Iron Casting Engine for Process Industry 1.1 kW, 3000 rpm, 230/400 V, B3 mount,..

Brand: ABB | Manufacturer Part Number: M3JP 80 MG



Manufacturer	ABB
MPN / Reference	M3JP 80 MG
Catalog number	3GJP081370-ASK
Category	ATEX motors M3GP, M3KP, M3JP
Minimum order	1 unit
Document ID	EO-CC0AB41C84
Generated	2026-08-04

Product Overview

M3JP 80MG 3GJP081370-ASK ABB Iron Casting Engine for Process Industry 1.1 kW, 3000 rpm, 230/400 V, B3 mount,..

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path ABB > ATEX motors M3GP, M3KP, M3JP

Additional Product Information

Product ID:3GJP081370-ASK

ABB Type Designation:M3JP 80MG 2

Catalog Description:Flameproof IE3 Premium Efficiency LV Motors, 1,1 kW, 400 V (3GJP081370-ASK)

Additional Information

ABB Type Designation:M3JP 80MG 2

Altitude:1000 m

Ambient Temperature:40 °C

Bearing:6205-2Z/C3

Bearing NDE:6204-2Z/C3

Connection Configuration:Y

Country of Origin:Finland (FI)

China (CN)

Poland (PL)

Customs Tariff Number:85015220

Direction of Rotation:Both sides

Electrical Data:Conn Temp Class Freq Voltage Power Speed Current Power Factor Efficiency Torque IS/IN

Y T4 50 Hz 400 V 1.10 kW 2862 r/min 2.10 A 0.870 82.70 % 3.65 N·m 6.30

D T4 50 Hz 230 V 1.10 kW 2862 r/min 3.70 A 0.870 82.70 % 3.65 N·m 6.30

Y T4 50 Hz 380 V 1.10 kW 2841 r/min 2.20 A 0.880 82.70 % 3.65 N·m 5.60

D T4 50 Hz 220 V 1.10 kW 2841 r/min 3.90 A 0.880 82.70 % 3.65 N·m 5.60

Y T4 50 Hz 415 V 1.10 kW 2873 r/min 2.10 A 0.860 82.70 % 3.65 N·m 6.70

Y T4 60 Hz 460 V 1.10 kW 3478 r/min 1.90 A 0.860 84.00 % 3.00 N·m 7.60

EX-Protection:Exdb

Frame Material:Cast Iron

Frame Size:80

Frequency (f):50 Hz

Gas Group:IIB

Gross Weight:52kg

IC Class:IC411

IE Class Data (50 Hz):IE Class IE3

Full Load (100%) 82.7 %

Partial Load (75%) 83.4 %

Partial Load (50%) 82.1 %

IE Class Data (60 Hz):IE Class IE3

Full Load (100%) 84.0 %

Partial Load (75%) 83.9 %

Partial Load (50%) 82.0 %

IM Class:IMB3 IM1001

Input Voltage (Uin):400 V

Insulation Class:ICLF

IP Rating:IP55

Made To Order:No

Medium Description:1.1kW, 2 Poles, Frame Size 80, 3 Phases, 400V, 50Hz, IP55 Enclos...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send ABB / M3JP 80 MG with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.