

INDUSTRIAL COMPONENT DATA

2CDS252001R0321 ABB Miniature Circuit Breaker S200 2P D 32 A

Brand: ABB | Manufacturer Part Number: 2CDS252001R0321



Manufacturer	ABB
MPN / Reference	2CDS252001R0321
Catalog number	252001
Category	Miniature circuit breaker (MCB)
Minimum order	1 Pcs
Document ID	EO-49AEAD2519
Generated	2026-08-03

Product Overview

Miniature Circuit Breaker - S200 - 2P - D - 32 A

Int.aut. S202-D32 2p 32A D 10kA

Miniature Circuit Breaker - S200 - 2P - 32 A - D - (AC) 6 kA

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path ABB > Tertiary / Industrial > S200

Additional Product Information

ABB EcoSolutions

ABB EcoSolutions Yes

EcoSolutions Profile 9AKK108469A3796

Recyclability Rate of the Product acc. to EN45555 Design for Closing Resource Loops - Standard EN45555 - 80.7 %

ABB Site Meeting Group Waste To Landfill Target No non-hazardous waste is sent to a landfill

Extended Product Lifetime Product Durability

Offered with Takeback Services Take Back for Recycling

End Of Life Disassembling Instructions 9AKK108468A3132

Environmental Product Declaration - EPD 9AKK108467A7832

Technical

Dielectric Test Voltage 50 / 60 Hz - 1 min 2 kV

Rated Ultimate Short-Circuit Breaking Capacity (Icu) (125 V DC) 10 kA
(230 V AC) 20 kA

(400 V AC) 10 kA
(440 V AC) 10 kA
(48 V DC) 20 kA
(230 V) 20 kA
(400 V) 10 kA
Rated Service Short-Circuit Breaking Capacity (Ics) (230 V AC) 15 kA
(400 V AC) 7.5 kA
(440 V AC) 7.5 kA
Power Supply Connection Arbitrary
Contact Position Indication Red ON / Green OFF
Energy Limiting Class 3
Electrical Endurance 10000 AC cycle
Mechanical Endurance 20000 cycle
Number of Protected Poles 2
Number of Poles 2P
Tightening Torque 2.8 N·m
Actuator Type Toggle
Screw Terminal Type Failsafe Bi-directional Cylinder-lift Terminal
Actuator Marking I / O
Actuator Material Insulation Group II, Black, Sealable
Recommended Screw Driver Pozidriv 2
Accessories Available Yes
Connecting Capacity Busbar 10/10 mm²
Flexible with Ferrule 0.75 ... 25 mm²
Flexible 0.75 ... 25 mm²
Rigid 0.75 ... 35 mm²
Rigid 0.75 ... 35 mm²
Stranded 0.75 ... 35 mm²
Installation Size acc. to DIN 43880....

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send ABB / 2CDS252001R0321 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.