

INDUSTRIAL COMPONENT DATA

2CDS282001R0034 ABB Miniature Circuit Breaker S200P 2P C 3 A

Brand: ABB | Manufacturer Part Number: 2CDS282001R0034



Manufacturer	ABB
MPN / Reference	2CDS282001R0034
Catalog number	282001
Category	Miniature circuit breaker (MCB)
Minimum order	1 Pcs
Document ID	EO-25A668E8B0
Generated	2026-08-05

Product Overview

Miniature Circuit Breaker - S200P - 2P - C - 3 A

Int.aut. S202P-C3 2p 3A C 25kA

Miniature Circuit Breaker - S200P - 2P - 3 A - C - (AC) 25 kA

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path ABB > Industrial > S200P

Additional Product Information

Technical

Dielectric Test Voltage 50 / 60 Hz - 1 min 2 kV

Rated Ultimate Short-Circuit Breaking Capacity (Icu) (230 V AC) 25 kA

(400 V AC) 25 kA

(400 V) 25 kA

Rated Service Short-Circuit Breaking Capacity (Ics) (400 V AC) 12.5 kA

Power Supply Connection Arbitrary

Contact Position Indication Red ON / Green OFF

Energy Limiting Class 3

Electrical Endurance 20000 AC cycle

Mechanical Endurance 20000 cycle

Number of Protected Poles 2

Number of Poles 2P

Tightening Torque 2.8 N·m
Screw Terminal Type Failsafe Bi-directional Cylinder-lift Terminal
Actuator Marking I / O
Actuator Material Insulation Group II, Black, Sealable
Recommended Screw Driver Pozidriv 2
Accessories Available Yes
Connecting Capacity Busbar 10/10 mm²
Flexible with Ferrule 0.75 ... 16 mm²
Flexible 0.75 ... 16 mm²
Rigid 0.75 ... 25 mm²
Stranded 0.75 ... 25 mm²
Installation Size acc. to DIN 43880 1
Terminal Type Screw Terminals
Electrical
Tripping Characteristic C
Rated Operational Voltage acc. to IEC 60898-1 400 V AC
acc. to IEC 60898-1 400 V
acc. to IEC 60947-2 400 V AC
Operational Voltage Maximum (Incl. Tolerance) 125 V DC
Maximum (Incl. Tolerance) 440 V AC
Minimum 12 V AC
Minimum 12 V DC
Rated Insulation Voltage (Ui) acc. to IEC/EN 60664-1 440 V
Rated Impulse Withstand Voltage (Uimp) 4 kV
at 2000 m 5 kV
at Sea Level 6.2 kV
Input Voltage Type AC/DC
Rated Current (In) 3 A
Rated Short-Circuit Capacity (AC) 25 kA
(230 V AC) 25 kA
(400 V AC) 25 kA
(400 V) 25 kA
Rated Conditional Short-Circuit Current (Inc) (230 V) 25....

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send ABB / 2CDS282001R0034 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.