

**INDUSTRIAL COMPONENT DATA**

# 2CDS213103R0064 ABB Miniature Circuit Breaker SH200 4P C 6 A

Brand: ABB | Manufacturer Part Number: 2CDS213103R0064



|                 |                                 |
|-----------------|---------------------------------|
| Manufacturer    | ABB                             |
| MPN / Reference | 2CDS213103R0064                 |
| Catalog number  | 213103                          |
| Category        | Miniature circuit breaker (MCB) |
| Minimum order   | 1 Pcs                           |
| Document ID     | EO-5E7C417D15                   |
| Generated       | 2026-08-05                      |

## Product Overview

Miniature Circuit Breaker - SH200 - 4P - C - 6 A  
Int.aut. SH203-C6NA 3p+N 6A C 6kA  
Miniature Circuit Breaker - SH200 - 3P+N - 6 A - C - (AC) 6 kA

**STRUCTURED PRODUCT DATA**

## Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

## Classification & Catalog Path

Catalog path **ABB > Residential / Tertiary > SH200**

## Additional Product Information

ABB EcoSolutions  
ABB EcoSolutions Yes  
EcoSolutions Profile 9AKK108471A1003  
Recyclability Rate of the Product acc. to EN45555 Design for Closing Resource Loops - Standard EN45555 - 92.1 %  
ABB Site Meeting Group Waste To Landfill Target No non-hazardous waste is sent to a landfill  
Extended Product Lifetime Product Durability  
End Of Life Disassembling Instructions 9AKK108468A3121  
Environmental Product Declaration - EPD 9AKK108468A1580  
Technical  
Dielectric Test Voltage 50 / 60 Hz - 1 min 2 kV  
Power Supply Connection Arbitrary  
Contact Position Indication ON / OFF  
Energy Limiting Class 3

Electrical Endurance 20000 AC cycle  
Mechanical Endurance 20000 cycle  
Number of Protected Poles 3  
Number of Poles 3P+N  
Position of Neutral Terminals Right  
Tightening Torque 2 N·m  
Actuator Type Toggle  
Screw Terminal Type Cage Terminal  
Actuator Marking I / O  
Actuator Material Insulation Group II, Black, Sealable  
Recommended Screw Driver Pozidriv 2  
Accessories Available No  
Connecting Capacity Conductor 25 / 25 mm<sup>2</sup>  
Flexible with Ferrule 0.75 ... 16 mm<sup>2</sup>  
Flexible 0.75 ... 16 mm<sup>2</sup>  
Rigid 0.75 ... 25 mm<sup>2</sup>  
Stranded 0.75 ... 25 mm<sup>2</sup>  
Installation Size acc. to DIN 43880 1  
Terminal Type Screw Terminals  
Electrical  
Tripping Characteristic C  
Rated Operational Voltage acc. to IEC 60898-1 400 V  
Operational Voltage Maximum (Incl. Tolerance) 440 V AC  
Minimum 12 V AC  
Rated Insulation Voltage (Ui) acc. to IEC/EN 60664-1 440 V  
Rated Impulse Withstand Voltage (Uimp) 4 kV  
at 2000 m 5 kV  
at Sea Level 6.2 kV  
Input Voltage Type A...

## REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send ABB / 2CDS213103R0064 with the required quantity to [info@electricaonline.com](mailto:info@electricaonline.com) or use [electricaonline.com/request-quote](https://electricaonline.com/request-quote).

### GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.