

**INDUSTRIAL COMPONENT DATA**

# 2CSS255101R0064 ABB Miniature circuit breaker SN201 2P C 6 A

Brand: ABB | Manufacturer Part Number: 2CSS255101R0064



|                 |                                 |
|-----------------|---------------------------------|
| Manufacturer    | ABB                             |
| MPN / Reference | 2CSS255101R0064                 |
| Catalog number  | 255101                          |
| Category        | Miniature circuit breaker (MCB) |
| Minimum order   | 1 Pcs                           |
| Document ID     | EO-1C09CC99ED                   |
| Generated       | 2026-08-01                      |

## Product Overview

Miniature circuit breaker - SN201 - 2P - C - 6 A  
Int.aut. SN201-C6 1p+N 6A C 6kA  
Miniature circuit breaker - SN201 - 1P+N - 6 A - C - (230 V) 6 kA

**STRUCTURED PRODUCT DATA**

## Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

## Classification & Catalog Path

|              |                                     |
|--------------|-------------------------------------|
| Catalog path | ABB > Tertiary / Industrial > SN200 |
|--------------|-------------------------------------|

## Additional Product Information

ABB EcoSolutions  
ABB EcoSolutions Yes  
EcoSolutions Profile 9AKK108471A1004  
Recyclability Rate of the Product acc. to EN45555 Design for Closing Resource Loops - Standard EN45555 - 90.63 %  
Sustainable Material Content in Packaging (wt. %) Recycled Paper - 00 %  
Recycled Cardboard - 79 %  
Extended Product Lifetime Product Durability  
End Of Life Disassembling Instructions 9AKK108469A7476  
Environmental Product Declaration - EPD 9AKK108469A9820  
Technical  
Dielectric Test Voltage 50 / 60 Hz - 1 min 2 kV  
Primary Rated Impulse Withstand Voltage 4 kV  
Rated Ultimate Short-Circuit Breaking Capacity (Icu) (230 V) 10 kA

Rated Service Short-Circuit Breaking Capacity (Ics) (230 V AC) 6 kA

Power Supply Connection Arbitrary

Contact Position Indication ON / OFF

Energy Limiting Class 3

Electrical Endurance 10000 cycle

Mechanical Endurance 20000 cycle

Number of Protected Poles 1

Number of Poles 1P+N

Number of Modular Spacings per DIN Rail 1

Position of Neutral Terminals Right

Tightening Torque 1.2 N·m

Actuator Type Toggle

Screw Terminal Type Cage Terminal

Accessories Available Yes

Connecting Capacity Flexible 1 ... 10 mm<sup>2</sup>

Rigid 1 ... 16 mm<sup>2</sup>

Wire Stripping Length 11 mm

Terminal Type Screw Terminals

Electrical

Tripping Characteristic C

Rated Voltage (Ur) 230 V AC

Rated Operational Voltage acc. to IEC 60898-1 230 V

Rated Insulation Voltage (Ui) acc. to IEC/EN 60664-1 500 V

Rated Impulse Withstand Voltage (Uimp) 4 kV

Input Voltage Type AC

Rated Current (In) 6 A

Rated Short-Circuit Capacity (230 V) 6 kA

Ra...

## REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send ABB / 2CSS255101R0064 with the required quantity to [info@electricaonline.com](mailto:info@electricaonline.com) or use [electricaonline.com/request-quote](https://electricaonline.com/request-quote).

### GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.