

INDUSTRIAL COMPONENT DATA

2CDS271337R0587 ABB Miniature Circuit Breaker SU200M 1P K 60 A

Brand: ABB | Manufacturer Part Number: 2CDS271337R0587



Manufacturer	ABB
MPN / Reference	2CDS271337R0587
Catalog number	271337
Category	Miniature circuit breaker (MCB)
Minimum order	1 Pcs
Document ID	EO-317F774D9F
Generated	2026-08-03

Product Overview

Miniature Circuit Breaker - SU200M - 1P - K - 60 A
Int.aut.SU201M-K60 1p 60A K UL489
Automatic switch - SU200M - 1P - 60 A - K - (230 V AC) 11.2 kA

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	ABB > Industrial > S200U
--------------	--------------------------

Additional Product Information

SU201M-K60 Miniature Circuit Breaker K-Char., 10kA, 60A, 1P UL489

Ordering

EAN:4016779930208

Minimum Order Quantity:1 piece

Customs Tariff Number:85362010

Dimensions

Product Net Width:17.5mm

Product Net Depth:69mm

Product Net Height:111mm

Product Net Weight:0.125kg

Container Information

Package Level 1 Units:10 piece

Package Level 1 Width:121 mm

Package Level 1 Length:191 mm

Package Level 1 Height:82 mm

Package Level 1 Gross Weight:1.3 kg

Package Level 1 EAN:4016779934466

Package Level 2 Units:72 piece

Package Level 2 Width:275 mm

Package Level 2 Length:395 mm

Package Level 2 Height:210 mm

Package Level 2 Gross Weight:16 kg

Package Level 2 EAN:4016779938266

Environmental

Ambient Air Temperature:Operation -25 ... +55 °C

Storage -40 ... +70 °C

Resistance to Shock acc. to IEC 60068-2-27:25g / 2 shocks / 13 ms

Resistance to Vibrations acc. to IEC 60068-2-6:5g, 20 cycles at 5 ... 150 ... 5 Hz with load 0.8 In

Environmental Conditions:28 cycles

with 55 °C / 90-96 %

and 25 °C / 95-100 %

Technical

Standards:CSA 22.2 No. 5

IEC/EN 60947-2

UL 489

Number of Poles:1

Tripping Characteristic:K

Rated Current (In):60 A

Rated Operational Voltage:acc. to IEC 60947-2 230 V AC

Power Loss:4,9 W

at Rated Operating Conditions per Pole 4,9 W

Rated Insulation Voltage (Ui):acc. to IEC/EN 60664-1 440 V

Rated Frequency (f):50 Hz

60 Hz

DC Hz

Rated Ultimate Short-Circuit Breaking Capacity (Icu):15 kA

Rated Service Short-Circuit Breaking Capacity (Ics):7.5 kA

Overvoltage Category:III

Pollution Degree:3

Rate...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send ABB / 2CDS271337R0587 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.