

INDUSTRIAL COMPONENT DATA

2CDS272337R0407 ABB Miniature Circuit Breaker SU200M 2P K 8 A

Brand: ABB | Manufacturer Part Number: 2CDS272337R0407



Manufacturer	ABB
MPN / Reference	2CDS272337R0407
Catalog number	272337
Category	Miniature circuit breaker (MCB)
Minimum order	1 Pcs
Document ID	EO-7E3817C2F2
Generated	2026-08-05

Product Overview

Miniature Circuit Breaker - SU200M - 2P - K - 8 A

Int.aut.SU202M-K8 2p 8A K UL489

Automatic switch - SU200M - 2P - 8 A - K - (400 V AC) 11.2 kA

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path ABB > Industrial > S200U

Additional Product Information

SU202M-K8 Miniature Circuit Breaker K-Char., 10kA, 8A, 2P UL489

Ordering

EAN:4016779932707

Minimum Order Quantity:1 piece

Customs Tariff Number:85362010

Dimensions

Product Net Width:35mm

Product Net Depth:69mm

Product Net Height:111mm

Product Net Weight:0.25kg

Container Information

Package Level 1 Units:5 piece

Package Level 1 Width:121 mm

Package Level 1 Length:191 mm

Package Level 1 Height:82 mm

Package Level 1 Gross Weight:1.3 kg

Package Level 1 EAN:4016779935296

Package Level 2 Units:36 piece

Package Level 2 Width:275 mm

Package Level 2 Length:395 mm

Package Level 2 Height:210 mm

Package Level 2 Gross Weight:16 kg

Package Level 2 EAN:4016779939096

Environmental

Ambient Air Temperature:Operation -25 ... +55 °C

Storage -40 ... +70 °C

Resistance to Shock acc. to IEC 60068-2-27:25g / 2 shocks / 13 ms

Resistance to Vibrations acc. to IEC 60068-2-6:5g, 20 cycles at 5 ... 150 ... 5 Hz with load 0.8 In

Environmental Conditions:28 cycles

with 55 °C / 90-96 %

and 25 °C / 95-100 %

Technical

Standards:CSA 22.2 No. 5

IEC/EN 60947-2

UL 489

Number of Poles:2

Tripping Characteristic:K

Rated Current (In):8 A

Rated Operational Voltage:acc. to IEC 60947-2 400 V AC

Power Loss:3 W

at Rated Operating Conditions per Pole 1,5 W

Rated Insulation Voltage (Ui):acc. to IEC/EN 60664-1 440 V

Rated Frequency (f):50 Hz

60 Hz

DC Hz

Rated Ultimate Short-Circuit Breaking Capacity (Icu):15 kA

Rated Service Short-Circuit Breaking Capacity (Ics):11.2 kA

Overvoltage Category:III

Pollution Degree:3

Rated Impuls...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send ABB / 2CDS272337R0407 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.