

INDUSTRIAL COMPONENT DATA

2CDS274337R0537 ABB Miniature Circuit Breaker SU200M 4P K 32 A

Brand: ABB | Manufacturer Part Number: 2CDS274337R0537

Manufacturer	ABB
MPN / Reference	2CDS274337R0537
Catalog number	274337
Category	Miniature circuit breaker (MCB)
Minimum order	1 Pcs
Document ID	EO-1C68090322
Generated	2026-08-05

Product Overview

Miniature Circuit Breaker - SU200M - 4P - K - 32 A

Int.aut.SU204M-K32 4p 32A K UL489

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path **ABB > Industrial > S200U**

Additional Product Information

SU204M-K32 Miniature Circuit Breaker K-Char., 10kA, 32A, 4P UL489

Ordering

EAN:4016779930680

Minimum Order Quantity:1 piece

Customs Tariff Number:85362010

Dimensions

Product Net Width:70mm

Product Net Depth:69mm

Product Net Height:111mm

Product Net Weight:0.5kg

Container Information

Package Level 1 Units:2 piece

Package Level 1 Width:121 mm

Package Level 1 Length:191 mm

Package Level 1 Height:82 mm
Package Level 1 Gross Weight:1.05 kg
Package Level 1 EAN:4016779937276
Package Level 2 Units:18 piece
Package Level 2 Width:275 mm
Package Level 2 Length:395 mm
Package Level 2 Height:210 mm
Package Level 2 Gross Weight:12.64 kg
Package Level 2 EAN:4016779941075
Environmental
Ambient Air Temperature:Operation -25 ... +55 °C
Storage -40 ... +70 °C
Resistance to Shock acc. to IEC 60068-2-27:25g / 2 shocks / 13 ms
Resistance to Vibrations acc. to IEC 60068-2-6:5g, 20 cycles at 5 ... 150 ... 5 Hz with load 0.8 In
Environmental Conditions:28 cycles
with 55 °C / 90-96 %
and 25 °C / 95-100 %
Technical
Standards:CSA 22.2 No. 5
IEC/EN 60947-2
UL 489
Number of Poles:4
Tripping Characteristic:K
Rated Current (In):32 A
Rated Operational Voltage:acc. to IEC 60947-2 400 V AC
Power Loss:14,8 W
at Rated Operating Conditions per Pole 3,7 W
Rated Insulation Voltage (Ui):acc. to IEC/EN 60664-1 440 V
Rated Frequency (f):50 Hz
60 Hz
DC Hz
Rated Ultimate Short-Circuit Breaking Capacity (Icu):15 kA
Rated Service Short-Circuit Breaking Capacity (Ics):11.2 kA
Overvoltage Category:III
Pollution Degree:3
Rat...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send ABB / 2CDS274337R0537 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.