

**INDUSTRIAL COMPONENT DATA**

# 2CDS212066R0324 ABB Miniature Circuit Breaker SV200

Brand: ABB | Manufacturer Part Number: 2CDS212066R0324



|                 |                                 |
|-----------------|---------------------------------|
| Manufacturer    | ABB                             |
| MPN / Reference | 2CDS212066R0324                 |
| Catalog number  | 212066                          |
| Category        | Miniature circuit breaker (MCB) |
| Minimum order   | 1 Pcs                           |
| Document ID     | EO-D49278A9F0                   |
| Generated       | 2026-08-03                      |

## Product Overview

Miniature Circuit Breaker - SV200  
Int.aut. SV202-C32 2p 32A C 6kA  
Miniature Circuit Breaker - SV200 - 2P - 32 A - C - (400 V AC) 6 kA

**STRUCTURED PRODUCT DATA**

## Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

## Classification & Catalog Path

Catalog path      ABB &gt; Residential / Tertiary &gt; SV200

## Additional Product Information

ABB EcoSolutions  
ABB EcoSolutions Yes  
EcoSolutions Profile 9AKK108471A1003  
Recyclability Rate of the Product acc. to EN45555 Design for Closing Resource Loops - Standard EN45555 - 92.1 %  
ABB Site Meeting Group Waste To Landfill Target No non-hazardous waste is sent to a landfill  
Extended Product Lifetime Product Durability  
End Of Life Disassembling Instructions 9AKK108468A3121  
Environmental Product Declaration - EPD 9AKK108468A1580  
Technical  
Energy Limiting Class 3  
Number of Protected Poles 2  
Number of Poles 2P  
Accessories Available No  
Connecting Capacity Flexible with Ferrule 0.75 ... 16 mm²

Flexible 0.75 ... 16 mm<sup>2</sup>

Rigid 0.75 ... 25 mm<sup>2</sup>

Stranded 0.75 ... 25 mm<sup>2</sup>

Electrical

Tripping Characteristic C

Rated Operational Voltage acc. to IEC 60898-1 400 V

Rated Insulation Voltage (Ui) acc. to IEC/EN 60664-1 440 V

Rated Impulse Withstand Voltage (Uimp) 4 kV

at 2000 m 5 kV

at Sea Level 6.2 kV

Input Voltage Type AC

Rated Current (In) 32 A

Rated Short-Circuit Capacity (400 V AC) 6 kA

(400 V) 6 kA

Rated Conditional Short-Circuit Current (Inc) (230 V) 6 kA

(400 V) 6 kA

Rated Frequency (f) 50 / 60 Hz

Overvoltage Category III

Material Compliance

RoHS Declaration 2CDK400646D2701

RoHS Information Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019

RoHS Date 20230209

REACH Declaration 9AKK107492A1906

REACH Information False - does not contain substances > 0.1 mass percentage

REACH Date 20251028

Conflict Minerals Reporting Template (CMRT) 9AKK108468A3363

WEEE Category 5. S...

## REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send ABB / 2CDS212066R0324 with the required quantity to [info@electricaonline.com](mailto:info@electricaonline.com) or use [electricaonline.com/request-quote](https://electricaonline.com/request-quote).

### GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.