

INDUSTRIAL COMPONENT DATA

1SCA022709R9680 ABB OS200D04N2P Switch fuse

Brand: ABB | Manufacturer Part Number: 1SCA022709R9680



Manufacturer	ABB
MPN / Reference	1SCA022709R9680
Catalog number	022709
Category	Fuse switch disconnecter
Minimum order	1 Pcs
Document ID	EO-BF40CF8E41
Generated	2026-08-03

Product Overview

OS200D04N2P Switch fuse
Fuse switch OS200D04N2P
OS200D04N2P SWITCH FUSE

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	ABB > Manual Switches > OS
--------------	----------------------------

Additional Product Information

Circular Value
Conflict Minerals Reporting Template (CMRT) 9AKK108467A5658
Environmental Product Declaration - EPD 1SCC311197D0201
Group Waste to Landfill Target UL 2799 Zero Waste To Landfill Validation available
REACH Declaration 1SCC011021D0201
RoHS Information 1SCC011020D0201
Toxic Substances Control Act - TSCA 1SCC011025D0201
Eco Transparency
Environmental Product Declaration - EPD 1SCC311197D0201
Ordering
Minimum Order Quantity 1 piece
Customs Tariff Number 85365080
Country of Origin Finland (FI)
Popular Downloads

Data Sheet, Technical Information 1SCC311013C0201

Instructions and Manuals 1SCC311012M0219

Environmental Product Declaration - EPD 1SCC311197D0201

Dimensions

Product Net Width 220 mm

Product Net Height 199 mm

Product Net Depth / Length 149 mm

Product Net Weight 4 kg

8.8 lb

Technical

Rated Operational Current AC-21A (Ie) (500 V) 200 A
(690 V) 200 A

Rated Operational Current AC-22A (Ie) (380 ... 415 V) 200 A
(500 V) 200 A
(690 V) 200 A

Rated Operational Current AC-23A (Ie) (380 ... 415 V) 200 A
(500 V) 200 A
(690 V) 200 A

Rated Operational Power AC-23A (Pe) (220 ... 240 V) 60 kW
(400 V) 110 kW
(415 V) 110 kW
(500 V) 132 kW
(690 V) 200 kW

Conventional Free-air Thermal Current (Ith) ? = 40 °C 200 A

Conventional Thermal Current (Ithe) Fully Enclosed 200 A

Rated Impulse Withstand Voltage (Uimp) 12 kV

Rated Insulation Voltage (Ui) 1000 V

Rated Operational Voltage Main Circuit 690 V AC

Rated Short-time Withstand Current Low Voltage (Icw) for 1 s 8 kiloampere rms
Rate...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send ABB / 1SCA022709R9680 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.