

INDUSTRIAL COMPONENT DATA

1SCA022860R6150 ABB OT1000E04P switch-disconnector

Brand: ABB | Manufacturer Part Number: 1SCA022860R6150



Manufacturer	ABB
MPN / Reference	1SCA022860R6150
Catalog number	022860
Category	Switch disconnector
Minimum order	1 Pcs
Document ID	EO-FC58D24435
Generated	2026-08-02

Product Overview

OT1000E04P switch-disconnector
OT1000E04P disconnect switch
OT1000E04P SWITCH-DISCONNECTOR

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	ABB > Manual Switches > OT
--------------	----------------------------

Additional Product Information

Circular Value
Conflict Minerals Reporting Template (CMRT) 9AKK108467A5658
End of Life Instructions 1SCC301120M0201
Environmental Information 1SCC301233D0201
Environmental Product Declaration - EPD 1SCC301300D0201
REACH Declaration 1SCC011021D0201
RoHS Information 1SCC011020D0201
Toxic Substances Control Act - TSCA 1SCC011025D0201
Eco Transparency
Environmental Product Declaration - EPD 1SCC301300D0201
Ordering
Minimum Order Quantity 1 piece
Customs Tariff Number 85365080
Country of Origin Finland (FI)

Popular Downloads

Data Sheet, Technical Information 1SCC301020C0201

Instructions and Manuals 1SCC301047M0213

Mechanical Drawings 1SCC301494F0001

1SCC301493F0001

OT1250E04.igs

Environmental Product Declaration - EPD 1SCC301300D0201

End of Life Instructions 1SCC301120M0201

Dimensions

Product Net Width 414.5 mm

Product Net Height 306 mm

Product Net Depth / Length 167 mm

Product Net Weight 19.5 kg

Technical

Rated Operational Current AC-21A (Ie) (380 ... 415 V) 1000 A
(500 V) 1000 A

(690 V) 1000 A

Rated Operational Current AC-22A (Ie) (380 ... 415 V) 1000 A
(500 V) 1000 A

(690 V) 1000 A

Rated Operational Current AC-23A (Ie) (380 ... 415 V) 1000 A
(500 V) 1000 A

(690 V) 1000 A

Rated Operational Power AC-23A (Pe) (400 ... 415 V) 560 kW
(500 V) 710 kW

(690 V) 1000 kW

Conventional Free-air Thermal Current (Ith) ? = 40 °C 1000 A

Conventional Thermal Current (Ithe) Fully Enclosed 1000 A

Rated Impulse Withstand Voltage (Uimp) 12 kV

Rated Insulation Voltage (Ui) acc. to IEC/EN 60664-1 1000...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send ABB / 1SCA022860R6150 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.