

INDUSTRIAL COMPONENT DATA

1SCA103308R1001 ABB OT1250E12CP CHANGE-OVER SWITCH

Brand: ABB | Manufacturer Part Number: 1SCA103308R1001



Manufacturer	ABB
MPN / Reference	1SCA103308R1001
Catalog number	103308
Category	Switch disconnecter
Minimum order	1 Pcs
Document ID	EO-81A0E798CE
Generated	2026-08-03

Product Overview

OT1250E12CP CHANGE-OVER SWITCH

OT1250E12CP switch

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path ABB > Manual Switches > OT_C

Additional Product Information

ABB EcoSolutions

End Of Life Disassembling Instructions 1SCC303053M0201

Environmental Information 1SCC303050D0201

Material Compliance

Conflict Minerals Reporting Template (CMRT) 9AKK108467A5658

REACH Declaration 1SCC011021D0201

RoHS Declaration 1SCC011020D0201

RoHS Information Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019

Popular Downloads

Data Sheet, Technical Information 1SCC303003C0201

Instructions and Manuals 1SCC303008M0208

Environmental

Degree of Protection Front IP20

Environmental Information 1SCC303050D0201

Pollution Degree 3

Ordering

Minimum Order Quantity 1 piece

Customs Tariff Number 85365080

Country or Territory of Origin Finland

Dimensions

Product Net Width 400 mm

15.75 in

Product Net Height 306 mm

12.05 in

Product Net Depth / Length 309 mm

12.17 in

Product Net Weight 48 kg

105.82 lb

Container Information

Package Level 1 Units box 1 box

Package Level 1 Width 500 mm

19.69 in

Package Level 1 Depth / Length 600 mm

23.62 in

Package Level 1 Height 550 mm

21.65 in

Package Level 1 Gross Weight 51 kg

112.44 lb

Package Level 1 EAN 6417019378220

Technical

Conventional Free-air Thermal Current (I_{th}) ? = 40 °C 1250 A

Degree of Protection Front IP20

Distance Between Phases Standard

Handle Color Black

Handle Type Handle and shaft included

Mounting Type Base mounting

Number of Poles 3P

Operating Mode Front

Pollution Degree 3

Position of Line Terminals Top In - Bottom Out, Bottom In - Top Out

Power Loss at Rated Operating Conditions per Pole 29 W

Rated....

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send ABB / 1SCA103308R1001 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.