

INDUSTRIAL COMPONENT DATA

OT160 Y 1SCA123569R1001 ABB OT160E13YP BY-PASS SWITCH

Brand: ABB | Manufacturer Part Number: OT160_Y



Manufacturer	ABB
MPN / Reference	OT160_Y
Catalog number	1SCA123569R1001
Category	Switch disconnecter
Minimum order	1 Pcs
Document ID	EO-6DCB4DC155
Generated	2026-08-03

Product Overview

OT160E13YP BY-PASS SWITCH
Bypas Manual Switch OT160E13YP

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path ABB > Manual Switches > OT_C

Additional Product Information

Including a black plastic IP65 I-0-II pistol type handle and a handle extension for enabling smooth manual operation, shaft and bolt set for the cable connection. The handle extension is snap-on mounted on the standard handle for manual operation. The handle extension shall be removed when padlocking the standard handle. Handle padlockable in the 0-position, door interlock in the I- and II-positions and when padlocked.

Ordering

EAN:6417019543536

Minimum Order Quantity:1 piece

Customs Tariff Number:85365080

Dimensions

Product Net Width:229mm

Product Net Height:150mm

Product Net Depth:236mm

Product Net Weight:7.5kg

Container Information

Package Level 1 Units:1 piece

Package Level 1 Width:175 mm

Package Level 1 Height:350 mm

Package Level 1 Length:360 mm

Package Level 1 Gross Weight:7.5 kg

Package Level 1 EAN:6417019543536

Environmental

RoHS Status:Planned to follow EU Directive 2002/95/EC August 18, 2005 and amendment after 2009 Q4

Additional Information

Conventional Free-air Thermal Current (Ith):q = 40 °C 160 A

Conventional Thermal Current (Ithe):Fully Enclosed 160 A

IIT Publishing Status:Level 0 - Information enabled

Number of Poles:4

Operating Mechanism:Mechanism between the poles

Pollution Degree:3

Power Loss:2.4 W

Product Main Type:OT160_Y

Product Name:BY-PASS SWITCH

Rated Impulse Withstand Voltage (Uimp):12 kV

Rated Insulation Voltage (Ui):1000 V

Rated Operational Current AC-21A (Ie):(500 V) 160 A
(690 V) 160 A

Rated Operational Current AC-22A (Ie):(500 V) 160 A
(690 V)...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send ABB / OT160_Y with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten PI #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.