

INDUSTRIAL COMPONENT DATA

1SCA022860R0710 ABB Int. Section. control side OT200ES04K

Brand: ABB | Manufacturer Part Number: 1SCA022860R0710



Manufacturer	ABB
MPN / Reference	1SCA022860R0710
Catalog number	022860
Category	Switch disconnecter
Minimum order	1 Pcs
Document ID	EO-5813B13443
Generated	2026-08-03

Product Overview

Int. Section. control side OT200ES04K
Int. Section. Side control OT200ES04K
OT200ES04K SWITCH-DISCONNECTOR

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path ABB > Manual Switches

Additional Product Information

Circular Value
Conflict Minerals Reporting Template (CMRT) 9AKK108467A5658
End of Life Instructions 1SCC301117M0201
Environmental Information 1SCC301265D0201
Environmental Product Declaration - EPD 1SCC301282D0201
REACH Declaration 1SCC011021D0201
RoHS Information 1SCC011020D0201
Toxic Substances Control Act - TSCA 1SCC011025D0201
Eco Transparency
Environmental Product Declaration - EPD 1SCC301282D0201
Ordering
Minimum Order Quantity 1 piece
Customs Tariff Number 85365080

Country of Origin Finland (FI)

Popular Downloads

Data Sheet, Technical Information 1SCC301020C0201

Instructions and Manuals 1SCC301068M0204

Mechanical Drawings 1SCC301654F0001

1SCC301653F0001

OT200ES04K.igs

Environmental Product Declaration - EPD 1SCC301282D0201

End of Life Instructions 1SCC301117M0201

Dimensions

Product Net Width 233.5 mm

Product Net Height 150 mm

Product Net Depth / Length 107 mm

Product Net Weight 2 kg

Technical

Rated Operational Current AC-21A (Ie) (380 ... 415 V) 200 A

(500 V) 200 A

(690 V) 200 A

(1000 V) 200 A

Rated Operational Current AC-22A (Ie) (380 ... 415 V) 200 A

(500 V) 200 A

(690 V) 200 A

Rated Operational Current AC-23A (Ie) (380 ... 415 V) 200 A

(500 V) 200 A

(690 V) 200 A

Rated Operational Power AC-23A (Pe) (220 ... 240 V) 60 kW

(400 ... 415 V) 110 kW

(500 V) 132 kW

(690 V) 200 kW

Conventional Free-air Thermal Current (Ith) ? = 40 °C 200 A

Conventional Thermal Current (Ithe) Fully Enclosed 200 A

Rated Impulse Withstand Voltage (Uimp) 12 kV

Rated Insulation Voltage (Ui) acc....

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send ABB / 1SCA022860R0710 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.