

INDUSTRIAL COMPONENT DATA

OT200KLAA6BZ 1SCA022717R9520 ABB OT200KLAA6BZ Enclosed switch

Brand: ABB | Manufacturer Part Number: OT200KLAA6BZ



Manufacturer	ABB
MPN / Reference	OT200KLAA6BZ
Catalog number	1SCA022717R9520
Category	Switch disconnecter
Minimum order	1 Pcs
Document ID	EO-A17163DA67
Generated	2026-08-04

Product Overview

OT200KLAA6BZ Enclosed switch
Int. Box disconnecter OT200KLAA6BZ
OT200KLAA6BZ Encl. Switch Disconnecter

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path **ABB > Manual Switches > Box**

Additional Product Information

ABB EcoSolutions
Material Compliance
RoHS Declaration 1SCC340049D0202
RoHS Information Following EU Directive 2011/65/EU
Popular Downloads
Data Sheet, Technical Information 1SCC340015C0201
Instructions and Manuals 1SCC340005M0007
Mechanical Drawings OTKM608023PO.stp
Environmental
Degree of Protection acc. to IEC 60529 IP65
Pollution Degree 3
Ordering
Minimum Order Quantity 1 piece

Customs Tariff Number 85363090

Replacement Product ID (NEW) OT200KLUU6BZ

Country or Territory of Origin Finland

Dimensions

Product Net Width 800 mm

Product Net Height 600 mm

Product Net Depth / Length 230 mm

Product Net Weight 24.5 kg

Container Information

Package Level 1 Units box 1 piece

Package Level 1 Width 815 mm

Package Level 1 Depth / Length 910 mm

Package Level 1 Height 325 mm

Package Level 1 Gross Weight 29 kg

Package Level 1 EAN 6417019230238

Technical

Cable Entry Position Up/Down

Cable Outlets Per Side Open / Open

Connecting Capacity Main Circuit Hole Diameter 8 mm

Screw Clamp / PE Terminal 8pcs, 10...70 mm²

Conventional Thermal Current (I_{the}) Fully Enclosed 200 A

Degree of Protection acc. to IEC 60529 IP65

Enclosure Material Steel sheet

Handle Color Black

Handle Type Pistol handle

Maximum Mounted Auxiliary Contacts 4 NO, 2 NC

Mounted Auxiliary Contacts 0 NO, 0 NC

Number of Poles 6P

Pollution Degree 3

Power Loss at Rated Operating Conditions per Pole 4 W

Rated Conditional Short-Circuit Current (I_{nc}) 40.5 kA

Rated Impulse Withstand Voltage (U_{imp}) 8 kV

Rated Insulation Voltage (U_i) acc. to I...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send ABB / OT200KLAA6BZ with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.