

INDUSTRIAL COMPONENT DATA

1SCA123577R1001 ABB OT250E22YP BY-PASS SWITCH

Brand: ABB | Manufacturer Part Number: 1SCA123577R1001



Manufacturer	ABB
MPN / Reference	1SCA123577R1001
Catalog number	123577
Category	Switch disconnecter
Minimum order	1 Pcs
Document ID	EO-C6BB020374
Generated	2026-08-01

Product Overview

OT250E22YP BY-PASS SWITCH
Manual Bypass Switch OT250E22YP

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	ABB > Manual Switches
--------------	-----------------------

Additional Product Information

Material Compliance

Conflict Minerals Reporting Template (CMRT) 9AKK108467A5658

REACH Declaration 1SCC011021D0201

RoHS Declaration 1SCC011020D0201

RoHS Information Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019

Popular Downloads

Data Sheet, Technical Information 1SCC303003C0201

Instructions and Manuals 1SCC301080M0003

Environmental

Degree of Protection Front IP20

Pollution Degree 3

Ordering

Minimum Order Quantity 1 piece

Customs Tariff Number 85365080

Country or Territory of Origin Finland

Dimensions

Product Net Width 229 mm

9.02 in

Product Net Height 150 mm

5.91 in

Product Net Depth / Length 236 mm

9.29 in

Product Net Weight 6.05 kg

13.34 lb

Container Information

Package Level 1 Units box 1 box

Package Level 1 Width 175 mm

Package Level 1 Depth / Length 360 mm

Package Level 1 Height 350 mm

Package Level 1 Gross Weight 6.56 kg

14.46 lb

Package Level 1 EAN 6417019543611

Technical

Conventional Free-air Thermal Current (Ith) ? = 40 °C 250 A

Conventional Thermal Current (Ithe) Fully Enclosed 250 A

Degree of Protection Front IP20

Distance Between Phases Standard

Fourth Pole Position Right Side

Fourth Pole Type Switched - Simultaneous Function

Handle Color Black

Handle Type Handle and shaft included

Mounting Type Base mounting

Number of Poles 4P

Operating Mode Front

Pollution Degree 3

Position of Line Terminals Top In - Bottom Out, Bottom In - Top Out

Power Loss at Rated Operating Conditions per Pole 6.5 W

Rated Impulse Withstand Voltage (Uimp) 12 kV

Rated....

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send ABB / 1SCA123577R1001 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten PI #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.