

INDUSTRIAL COMPONENT DATA

1SCA123583R1001 ABB OT315E04YP BY-PASS SWITCH

Brand: ABB | Manufacturer Part Number: 1SCA123583R1001



Manufacturer	ABB
MPN / Reference	1SCA123583R1001
Catalog number	123583
Category	Switch disconnecter
Minimum order	1 Pcs
Document ID	EO-1D6AF7B87E
Generated	2026-07-31

Product Overview

OT315E04YP BY-PASS SWITCH
Manual Bypass Switch OT315E04YP

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	ABB > Manual Switches
--------------	-----------------------

Additional Product Information

Material Compliance

Conflict Minerals Reporting Template (CMRT) 9AKK108467A5658

REACH Declaration 1SCC011021D0201

RoHS Declaration 1SCC011020D0201

RoHS Information Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019

Popular Downloads

Data Sheet, Technical Information 1SCC303003C0201

Instructions and Manuals 1SCC301080M0003

Environmental

Degree of Protection Front IP20

Pollution Degree 3

Ordering

Minimum Order Quantity 1 piece

Customs Tariff Number 85365080

Country or Territory of Origin Finland

Dimensions

Product Net Width 284 mm

11.18 in

Product Net Height 185 mm

7.28 in

Product Net Depth / Length 306 mm

12.05 in

Product Net Weight 13.6 kg

29.98 lb

Container Information

Package Level 1 Units box 1 box

Package Level 1 Width 265 mm

10.43 in

Package Level 1 Depth / Length 375 mm

14.76 in

Package Level 1 Height 330 mm

12.99 in

Package Level 1 Gross Weight 14.02 kg

30.91 lb

Package Level 1 EAN 6417019543673

TechnicalConventional Free-air Thermal Current (I_{th}) ? = 40 °C 315 AConventional Thermal Current (I_{the}) Fully Enclosed 315 A

Degree of Protection Front IP20

Distance Between Phases Standard

Fourth Pole Position Right Side

Fourth Pole Type Switched - Simultaneous Function

Handle Color Black

Handle Type Handle and shaft included

Mounting Type Base mounting

Number of Poles 4P

Operating Mode Front

Pollution Degree 3

Position of Line Terminals Top In - Bottom Out, Bottom In - Top Out

Power Loss at Rated Operating Conditions per Pole 6.5 W

Rated Impulse Withsta...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send ABB / 1SCA123583R1001 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.