

INDUSTRIAL COMPONENT DATA

1SCA022834R0110 ABB Int. Disconnecter in box OT315KFCC3BA

Brand: ABB | Manufacturer Part Number: 1SCA022834R0110



Manufacturer	ABB
MPN / Reference	1SCA022834R0110
Catalog number	022834
Category	Switch disconnecter
Minimum order	1 Pcs
Document ID	EO-95C3430F4F
Generated	2026-08-02

Product Overview

Int. Disconnecter in box OT315KFCC3BA
Int. Box Disconnect OT315KFCC3BA
OT315KFCC3BA Encl. Switch Disconnecter

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path **ABB > Manual Switches**

Additional Product Information

Material Compliance
Conflict Minerals Reporting Template (CMRT) 9AKK108467A5658
REACH Declaration 1SCC340076D0201
RoHS Declaration 1SCC340075D0201
RoHS Information Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019
Toxic Substances Control Act - TSCA 1SCC340095D0201
Popular Downloads
Data Sheet, Technical Information 1SCC340015C0201
Instructions and Manuals 1SCC340015M0004
Mechanical Drawings OTPK563818PIL.stp
Environmental
Degree of Protection acc. to IEC 60529 IP65
Pollution Degree 3

Ordering

Minimum Order Quantity 1 piece

Customs Tariff Number 85363090

Country or Territory of Origin Finland

Dimensions

Product Net Width 380 mm

Product Net Height 560 mm

Product Net Depth / Length 180 mm

Product Net Weight 7.766 kg

Container Information

Package Level 1 Units box 1 piece

Package Level 1 Width 415 mm

Package Level 1 Depth / Length 710 mm

Package Level 1 Height 325 mm

Package Level 1 Gross Weight 9.7 kg

Package Level 1 EAN 6417019289380

Technical

Cable Entry Position Top/Bottom

Cable Outlets Per Side II-flange / II-flange

Color RAL7035

Connecting Capacity Main Circuit Hole Diameter 10 mm

Screw Clamp / PE Terminal 4pc, 25 ... 120 mm²Conventional Thermal Current (I_{the}) Fully Enclosed 315 A

Degree of Protection acc. to IEC 60529 IP65

Enclosure Material Plastic

Handle Color Red / Yellow

Handle Type Pistol handle

Impact Resistance Rating Housing IK08

Maximum Mounted Auxiliary Contacts 2 NO, 2 NC

Mounted Auxiliary Contacts 0 NO, 0 NC

Neutral Type Detachable Neutra...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send ABB / 1SCA022834R0110 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.