

INDUSTRIAL COMPONENT DATA

1SCA123593R1001 ABB OT800E04YP BY-PASS SWITCH

Brand: ABB | Manufacturer Part Number: 1SCA123593R1001



Manufacturer	ABB
MPN / Reference	1SCA123593R1001
Catalog number	123593
Category	Switch disconnecter
Minimum order	1 Pcs
Document ID	EO-D5EF73F31A
Generated	2026-07-29

Product Overview

OT800E04YP BY-PASS SWITCH
Manual Bypass Switch OT800E04YP

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	ABB > Manual Switches
--------------	-----------------------

Additional Product Information

Material Compliance

Conflict Minerals Reporting Template (CMRT) 9AKK108467A5658

REACH Declaration 1SCC011021D0201

RoHS Declaration 1SCC011020D0201

RoHS Information Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019

Popular Downloads

Data Sheet, Technical Information 1SCC303003C0201

Instructions and Manuals 1SCC301080M0003

Environmental

Degree of Protection Front IP20

Pollution Degree 3

Ordering

Minimum Order Quantity 1 piece

Customs Tariff Number 85365080

Country or Territory of Origin Finland

Dimensions

Product Net Width 380 mm

14.96 in

Product Net Height 250 mm

9.84 in

Product Net Depth / Length 432 mm

17.01 in

Product Net Weight 33.56 kg

73.99 lb

Container Information

Package Level 1 Units box 1 box

Package Level 1 Width 394 mm

Package Level 1 Depth / Length 368 mm

Package Level 1 Height 534 mm

Package Level 1 Gross Weight 35.61 kg

Package Level 1 EAN 6417019543772

TechnicalConventional Free-air Thermal Current (I_{th}) ? = 40 °C 800 AConventional Thermal Current (I_{the}) Fully Enclosed 800 A

Degree of Protection Front IP20

Distance Between Phases Standard

Fourth Pole Position Right Side

Fourth Pole Type Switched - Simultaneous Function

Handle Color Black

Handle Type Handle and shaft included

Mounting Type Base mounting

Number of Poles 4P

Operating Mode Front

Pollution Degree 3

Position of Line Terminals Top In - Bottom Out, Bottom In - Top Out

Power Loss at Rated Operating Conditions per Pole 40 W

Rated Impulse Withstand Voltage (U_{imp}) 12 kV

Rated Insula...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send ABB / 1SCA123593R1001 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.