

## INDUSTRIAL COMPONENT DATA

# OTDC320UV12 1SCA142256R1001 ABB OTDC320UV12 PV Disconnect Switch

Brand: ABB | Manufacturer Part Number: OTDC320UV12



|                 |                     |
|-----------------|---------------------|
| Manufacturer    | ABB                 |
| MPN / Reference | OTDC320UV12         |
| Catalog number  | 1SCA142256R1001     |
| Category        | Switch disconnector |
| Minimum order   | 1 Pcs               |
| Document ID     | EO-43C86A4143       |
| Generated       | 2026-07-28          |

## Product Overview

OTDC320UV12 PV Disconnect Switch  
DC disconnect switch OTDC320UV12

## STRUCTURED PRODUCT DATA

## Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

## Classification & Catalog Path

|              |                       |
|--------------|-----------------------|
| Catalog path | ABB > Manual Switches |
|--------------|-----------------------|

## Additional Product Information

OTDC320UV12 PV Disconnect Switch, Terminal bolt kit included, Handle and shaft need to be ordered separately, Base mounting, 1500 V pre-connected, UL 1000 VDC 320 A, UL 1500 VDC 320 A, IEC 1500 VDC 400 A

### Ordering

Minimum Order Quantity:1 piece

Customs Tariff Number:85365080

### Popular Downloads

Data Sheet, Technical Information:1SCC301021C0201

### Dimensions

Product Net Width:266mm

Product Net Height:227mm

Product Net Depth:105mm

Product Net Weight:4,7kg

### Technical

Rated Operational Current DC-21B (Ie):(1500 V) 400 A

Conventional Free-air Thermal Current (I<sub>th</sub>): q = 40 °C 400 A  
Conventional Thermal Current (I<sub>the</sub>): Fully Enclosed 400 A  
Rated Impulse Withstand Voltage (U<sub>imp</sub>): 12 kV  
Rated Insulation Voltage (U<sub>i</sub>): 1500 V  
Rated Operational Voltage: 1500 V  
Rated Short-time Withstand Current (I<sub>cw</sub>): for 1 s 10 kiloampere rms  
Pollution Degree: 3  
Handle Type: Handle and shaft not included  
Switches Operating Mechanism: Mechanism Between the Poles  
12 (Between the Poles)  
Operating Mode: Front Operated  
Standards: IEC&UL  
Special Functions: 1500 V pre-connected  
Mounting Type: Base mounting  
Number of Circuits: 1  
Number of Poles: 3  
Terminal Type: Lug terminals  
Technical UL/CSA  
Ampere Rating UL/CSA: 1000 VDC 320 A  
1500 VDC 320 A  
Container Information  
Package Level 1 Gross Weight: 5.1 kg  
Package Level 1 EAN: 6417019697024  
Classifications  
ETIM 5: EC000216 - Switch disconnecter  
ETIM 6: EC000216 - Switch disconnecter

## REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send ABB / OTDC320UV12 with the required quantity to [info@electricaonline.com](mailto:info@electricaonline.com) or use [electricaonline.com/request-quote](https://electricaonline.com/request-quote).

### GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.