

INDUSTRIAL COMPONENT DATA

1SCA115369R1001 ABB OTM1600E4M230C Motorized switch-disconnector

Brand: ABB | Manufacturer Part Number: 1SCA115369R1001



Manufacturer	ABB
MPN / Reference	1SCA115369R1001
Catalog number	115369
Category	Switch disconnector
Minimum order	1 Pcs
Document ID	EO-B90776D11F
Generated	2026-08-01

Product Overview

OTM1600E4M230C Motorized switch-disconnector
Int. disconnector Motor OTM1600E4M230C
OTM1600E4M230C MOTORIZED SWITCH

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path **ABB > Manual Switches > OT**

Additional Product Information

ABB EcoSolutions
End Of Life Disassembling Instructions 1SCC301141M0201
Environmental Product Declaration - EPD 1SCC303101D0201
Material Compliance
Conflict Minerals Reporting Template (CMRT) 9AKK108467A5658
REACH Declaration 1SCC011021D0201
RoHS Declaration 1SCC011020D0201
RoHS Information Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019
Toxic Substances Control Act - TSCA 1SCC011025D0201
Popular Downloads
Data Sheet, Technical Information 1SCC301020C0201
Instructions and Manuals 1SCC303006M0205
Environmental Product Declaration - EPD 1SCC303101D0201

Environmental

Degree of Protection Front IP00

Pollution Degree 3

Ordering

Minimum Order Quantity 1 piece

Customs Tariff Number 85365080

Country or Territory of Origin Finland

Dimensions

Product Net Width 586.5 mm

Product Net Height 372 mm

Product Net Depth / Length 153 mm

Product Net Weight 30 kg

Container Information

Package Level 1 Units box 1 piece

Package Level 1 Width 435 mm

Package Level 1 Depth / Length 673 mm

Package Level 1 Height 215 mm

Package Level 1 Gross Weight 32 kg

Package Level 1 EAN 6417019477398

Technical

Conventional Free-air Thermal Current (Ith) ? = 40 °C 1600 A

Conventional Thermal Current (Ithe) Fully Enclosed 1600 A

Degree of Protection Front IP00

Distance Between Phases Standard

Fourth Pole Position Right Side

Fourth Pole Type Switched - Simultaneous Function

Handle Color Black

Handle Type Direct mounted handle

Mechanical Durability 6000

Motor Operational Voltage 220 ... 240 V AC....

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send ABB / 1SCA115369R1001 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.