

INDUSTRIAL COMPONENT DATA

1SCA115283R1001 ABB OTM160E3M230C Motorized switch-disconnector

Brand: ABB | Manufacturer Part Number: 1SCA115283R1001



Manufacturer	ABB
MPN / Reference	1SCA115283R1001
Catalog number	115283
Category	Switch disconnector
Minimum order	1 Pcs
Document ID	EO-C42F50496D
Generated	2026-08-01

Product Overview

OTM160E3M230C Motorized switch-disconnector

Int. disconnector Motor OTM160E3M230C

OTM160E3M230C MOTORIZED SWITCH

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path ABB > Manual Switches > OT

Additional Product Information

ABB EcoSolutions

End Of Life Disassembling Instructions 1SCC301138M0201

Environmental Product Declaration - EPD 1SCC303093D0201

Material Compliance

Conflict Minerals Reporting Template (CMRT) 9AKK108467A5658

REACH Declaration 1SCC011021D0201

RoHS Declaration 1SCC011020D0201

RoHS Information Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019

Toxic Substances Control Act - TSCA 1SCC011025D0201

Popular Downloads

Data Sheet, Technical Information 1SCC301020C0201

Instructions and Manuals 1SCC303006M0205

Environmental Product Declaration - EPD 1SCC303093D0201

Environmental

Degree of Protection Front IP00

Pollution Degree 3

Ordering

Minimum Order Quantity 1 piece

Customs Tariff Number 85365080

Country or Territory of Origin Finland

Dimensions

Product Net Width 296 mm

Product Net Height 150 mm

Product Net Depth / Length 198 mm

Product Net Weight 5.1 kg

Container Information

Package Level 1 Units box 1 piece

Package Level 1 Width 215 mm

Package Level 1 Depth / Length 395 mm

Package Level 1 Height 215 mm

Package Level 1 Gross Weight 6 kg

Package Level 1 EAN 6417019476711

Technical

Conventional Free-air Thermal Current (Ith) ? = 40 °C 200 A

Conventional Thermal Current (Ithe) Fully Enclosed 160 A

Degree of Protection Front IP00

Distance Between Phases Standard

Handle Color Black

Handle Type Direct mounted handle

Mechanical Durability 20000

Motor Operational Voltage 220 ... 240 V AC

Mounting Type Base mounting

Number of Poles 3P

Operating Mode Front

Pollution Degree....

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send ABB / 1SCA115283R1001 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.