


INDUSTRIAL COMPONENT DATA

1SCA129240R1001 ABB Int. Switch Engine OTM3200E3CM230C

Brand: ABB | Manufacturer Part Number: 1SCA129240R1001



Manufacturer	ABB
MPN / Reference	1SCA129240R1001
Catalog number	129240
Category	Switch disconnecter
Minimum order	1 Pcs
Document ID	EO-5FDE26A6D8
Generated	2026-08-02

Product Overview

Int. Switch Engine OTM3200E3CM230C
Int. Motor Commutator OTM3200E3CM230C
OTM3200E3CM230C MOTORIZED C/O SWITCH

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path **ABB > Manual Switches**

Additional Product Information

ABB EcoSolutions
End Of Life Disassembling Instructions 1SCC303062M0201
Environmental Product Declaration - EPD 1SCC303114D0201
Material Compliance
Conflict Minerals Reporting Template (CMRT) 9AKK108467A5658
REACH Declaration 1SCC011021D0201
RoHS Declaration 1SCC011020D0201
RoHS Information Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019
Popular Downloads
Data Sheet, Technical Information 1SCC303003C0201
Instructions and Manuals 1SCC303002M0204
Environmental Product Declaration - EPD 1SCC303114D0201
Ordering

Minimum Order Quantity 1 piece

Customs Tariff Number 85365080

Country or Territory of Origin Finland

Dimensions

Product Net Width 691.5 mm

27.22 in

Product Net Height 410 mm

16.14 in

Product Net Depth / Length 429 mm

16.89 in

Product Net Weight 61 kg

134.48 lb

Container Information

Package Level 1 Units box 1 box

Package Level 1 Width 780 mm

30.7 in

Package Level 1 Depth / Length 580 mm

22.8 in

Package Level 1 Height 500 mm

19.7 in

Package Level 1 Gross Weight 81 kg

178.5 lb

Package Level 1 EAN 6417019589374

Technical

Conventional Free-air Thermal Current (I_{th}) ? = 40 °C 3200 A

Distance Between Phases Standard

Handle Type Direct mounted handle

Motor Operational Voltage 220 ... 240 V AC

Mounting Type Base mounting

Number of Poles 3P

Operating Mode Front

Position of Line Terminals Top In - Bottom Out, Bottom In - Top Out

Power Loss at Rated Operating Conditions per Pole 95 W

Rated Operational Current AC-21B (I_e) (380 ... 415 V) 3200 A
(500 V) 3200 A....

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send ABB / 1SCA129240R1001 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.