

INDUSTRIAL COMPONENT DATA

1SCA022459R6600 ABB OTP25BA4M Enclosed switch

Brand: ABB | Manufacturer Part Number: 1SCA022459R6600



Manufacturer	ABB
MPN / Reference	1SCA022459R6600
Catalog number	022459
Category	Switch disconnecter
Minimum order	1 Pcs
Document ID	EO-D12C9CB142
Generated	2026-08-03

Product Overview

OTP25BA4M Enclosed switch
Int. Box disconnecter OTP25BA4M
OTP25BA4M Enclosed Switch Disconnecter

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	ABB > Manual Switches > Box
--------------	-----------------------------

Additional Product Information

Circular Value
Conflict Minerals Reporting Template (CMRT) 9AKK108467A5658
REACH Declaration 1SCC340076D0201
RoHS Information 1SCC340075D0201
Toxic Substances Control Act - TSCA 1SCC340095D0201
Ordering
Minimum Order Quantity 1 piece
Customs Tariff Number 85363030
Country of Origin Finland (FI)
Popular Downloads
Data Sheet, Technical Information 1SCC340015C0201
Instructions and Manuals 1SCC340002M0012
Mechanical Drawings OTPK151385SM25.stp
Dimensions

Product Net Width 130 mm

Product Net Height 150 mm

Product Net Depth / Length 60 mm

Product Net Weight 0.635 kg

Technical

Rated Operational Current AC-21A (Ie) (500 V) 25 A

(380 ... 415 V) 25 A

(690 V) 25 A

Rated Operational Current AC-22A (Ie) (380 ... 415 V) 25 A

(690 V) 25 A

Rated Operational Current AC-23A (Ie) (380 ... 415 V) 20 A

(500 V) 20 A

(690 V) 11 A

Rated Operational Power AC-23A (Pe) (380 ... 415 V) 9 kW

(500 V) 9 kW

(690 V) 9 kW

Conventional Thermal Current (Ithe) Fully Enclosed 32 A

Rated Impulse Withstand Voltage (Uimp) 0.5 kV

Rated Insulation Voltage (Ui) acc. to IEC/EN 60664-1 750 V

Rated Operational Voltage Main Circuit 750 V

Rated Short-Circuit Making Capacity (Icm) (690 V AC) 0.705 kA

Rated Short-time Withstand Current Low Voltage (Icw) for 1 s 0.5 kA

Power Loss at Rated Operating Conditions per Pole 0.6 W

Pollution Degree 3

Handle Color Red / Yellow

Handle Type Selector handle

Position of Line Terminals Top In - Bottom Out

Standards IEC 60947-1, -3

Number of Poles 4

Neutral Type Fixed and switchable neutral...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send ABB / 1SCA022459R6600 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.