

INDUSTRIAL COMPONENT DATA

2CCS573001R0257 ABB S403M-K1.6 Miniature Circuit Breaker 3 Poles K Characteristic 1,6A 50000 ~230/400V

Brand: ABB | Manufacturer Part Number: 2CCS573001R0257



Manufacturer	ABB
MPN / Reference	2CCS573001R0257
Catalog number	50000
Category	Miniature circuit breaker (MCB)
Minimum order	1 Pcs
Document ID	EO-F10A465D40
Generated	2026-08-06

Product Overview

S403M-K1.6 Miniature Circuit Breaker 3 Poles K Characteristic 1,6A 50000 ~230/400V

SMISLINE-I. Aut S403M K 1.6 A APR

Miniature Circuit Breaker - S400 - 3P - 1.6 A - K - (230 V) 10 kA

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path ABB > Industrial > SMISLINE

Additional Product Information

ABB EcoSolutions

ABB EcoSolutions Yes

EcoSolutions Profile 9AKK108469A7869

Recyclability Rate of the Product acc. to EN45555 Design for Closing Resource Loops - Standard EN45555 - 92.73 %

ABB Site Meeting Group Waste To Landfill Target No non-hazardous waste is sent to a landfill

Sustainable Material Content in Packaging (wt. %) Recycled Cardboard - 18.12 %

Recycled Cardboard - 67.66 %

Chemically Recycled Polymer - 0 %

Extended Product Lifetime Product Durability

End Of Life Disassembling Instructions 9AKK108469A6908

Environmental Product Declaration - EPD 9AKK108469A5735

Technical

Rated Operational Current (Ie) 1.6 A

Rated Ultimate Short-Circuit Breaking Capacity (Icu) (230 / 400 V AC) 50 kA

Rated Short-Circuit Making Capacity (Icm) (440 V AC) 30 kA

(415 V AC) 52.2 kA

Rated Service Short-Circuit Breaking Capacity (Ics) (240 V AC) 15 kA

(415 V AC) 15 kA

(440 V AC) 7.5 kA

Rated Service Short-Circuit Breaking Capacity, in % of Icu (Ics) 50 %

Power Supply Connection Arbitrary

Contact Position Indication Red ON / Green OFF

Energy Limiting Class 3

Electrical Endurance 10000 cycle

Mechanical Endurance 10000 cycle

Number of Protected Poles 3

Number of Poles 3P

Tightening Torque 2.8 N·m

Release Type K

Screw Terminal Type Failsafe Bi-directional Cylinder-lift Terminal

Actuator Marking I / O

Recommended Screw Driver Pozidriv 2

Accessories Available Yes

Connecting Capacity Flexible 0.75 ... 25 mm²

Rigid 0.75 ... 35 mm²

Terminal Type Screw Terminals

Electrical

Tripping Characteristic K

Rate...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send ABB / 2CCS573001R0257 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.