

## INDUSTRIAL COMPONENT DATA

# 2CCS811001R0631 ABB S801B-D63 High Performance Circuit Breaker

Brand: ABB | Manufacturer Part Number: 2CCS811001R0631



|                 |                                 |
|-----------------|---------------------------------|
| Manufacturer    | ABB                             |
| MPN / Reference | 2CCS811001R0631                 |
| Catalog number  | 811001                          |
| Category        | Miniature circuit breaker (MCB) |
| Minimum order   | 1 Pcs                           |
| Document ID     | EO-13D22EA9AD                   |
| Generated       | 2026-08-03                      |

## Product Overview

S801B-D63 High Performance Circuit Breaker

Int.aut. S801B-D63 1p 63A D 16kA

S801B-D63 High Performance MCB

## STRUCTURED PRODUCT DATA

## Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

## Classification & Catalog Path

Catalog path ABB &gt; Industrial &gt; S800C

## Additional Product Information

ABB EcoSolutions

ABB EcoSolutions Yes

EcoSolutions Profile 9AKK108471A1082

Recyclability Rate of the Product acc. to EN45555 Design for Closing Resource Loops - Standard EN45555 - 86.29 %

ABB Site Meeting Group Waste To Landfill Target No non-hazardous waste is sent to a landfill

End Of Life Disassembling Instructions 9AKK108470A2575

Environmental Product Declaration - EPD 9AKK108470A1695

9AKK108470A1696

Technical

Rated Ultimate Short-Circuit Breaking Capacity (Icu) (230 V AC) 16 kA  
(75 V DC) 10 kARated Service Short-Circuit Breaking Capacity (Ics) (230 V AC) 10 kA  
(75 V DC) 10 kA

Contact Position Indication ON / OFF / TRIP  
Energy Limiting Class 3  
Number of Protected Poles 1  
Number of Poles 1P  
Tightening Torque 3.5 N·m  
Release Type B  
Actuator Marking I / O  
Recommended Screw Driver Pozidriv 2  
Accessories Available Yes  
Remarks Connection from top and bottom  
Connecting with CU only  
IP40 in enclosure with cover  
Cage terminal with captive screw  
Connecting Capacity Flexible 0 ... 50 mm<sup>2</sup>  
Rigid 0 ... 70 mm<sup>2</sup>  
Terminal Type Screw Terminals  
Electrical  
Tripping Characteristic D  
Rated Operational Voltage acc. to IEC 60898-1 230 V AC  
acc. to IEC 60947-2 230 V AC  
Rated Insulation Voltage (Ui) acc. to IEC/EN 60664-1 500 V  
Rated Impulse Withstand Voltage (Uimp) 6 kV  
Input Voltage Type AC/DC  
Rated Current (In) 63 A  
Rated Short-Circuit Capacity (230 / 400 V AC) 10 kA  
Frequency (f) 50...60 Hz  
Rated Frequency (f) 50/60 Hz  
Power Loss 6.4 W  
at Rated Operating Conditions per Pole 6.4 W  
Overvoltage Cat...

## REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send ABB / 2CCS811001R0631 with the required quantity to [info@electricaonline.com](mailto:info@electricaonline.com) or use [electricaonline.com/request-quote](https://electricaonline.com/request-quote).

### GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.