

**INDUSTRIAL COMPONENT DATA**

# 2CCS861001R0085 ABB S801S-B8 High Performance Circuit Breaker

Brand: ABB | Manufacturer Part Number: 2CCS861001R0085



|                 |                                 |
|-----------------|---------------------------------|
| Manufacturer    | ABB                             |
| MPN / Reference | 2CCS861001R0085                 |
| Catalog number  | 861001                          |
| Category        | Miniature circuit breaker (MCB) |
| Minimum order   | 1 Pcs                           |
| Document ID     | EO-789F568371                   |
| Generated       | 2026-08-03                      |

## Product Overview

S801S-B8 High Performance Circuit Breaker

Int. aut. S801S-B8 1p 8A B 50kA

S801S-B8 High Performance MCB

**STRUCTURED PRODUCT DATA**

## Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

## Classification & Catalog Path

|              |                          |
|--------------|--------------------------|
| Catalog path | ABB > Industrial > S800S |
|--------------|--------------------------|

## Additional Product Information

ABB EcoSolutions

ABB EcoSolutions Yes

EcoSolutions Profile 9AKK108471A1082

Recyclability Rate of the Product acc. to EN45555 Design for Closing Resource Loops - Standard EN45555 - 86.29 %

ABB Site Meeting Group Waste To Landfill Target No non-hazardous waste is sent to a landfill

End Of Life Disassembling Instructions 9AKK108470A2575

Environmental Product Declaration - EPD 9AKK108470A1695

9AKK108470A1696

Technical

Rated Ultimate Short-Circuit Breaking Capacity (Icu) (240 V AC) 50 kA

(254 V AC) 30 kA

(289 / 500 V AC) 15 kA

(400 V AC) 6 kA

(125 V DC) 30 kA  
Rated Service Short-Circuit Breaking Capacity (Ics) (240 V AC) 40 kA  
(254 V AC) 22.5 kA  
(289 / 500 V AC) 11 kA  
(400 V AC) 4 kA  
(125 V DC) 30 kA  
Contact Position Indication ON / OFF / TRIP  
Energy Limiting Class 3  
Electrical Endurance 10000 cycle  
Mechanical Endurance 10000 cycle  
Number of Protected Poles 1  
Number of Poles 1P  
Tightening Torque 3.5 N·m  
Release Type B  
Actuator Marking I / O  
Recommended Screw Driver Pozidriv 2  
Accessories Available Yes  
Remarks Connection from top and bottom  
Connecting with CU only  
IP40 in enclosure with cover  
Cage terminal with captive screw  
Connecting Capacity Flexible 0 ... 50 mm<sup>2</sup>  
Rigid 0 ... 70 mm<sup>2</sup>  
Terminal Type Screw Terminals  
Electrical  
Tripping Characteristic B  
Rated Operational Voltage acc. to IEC 60898-1 230 V AC  
acc. to IEC 60947-2 400 V AC  
Rated Insulation Voltage (Ui) acc. to IEC/EN 60664-1 690 V  
Rated Impulse Withstand Voltage (Uimp) 8 kV  
Input Voltage Type AC/DC  
Rated Current (In) 8 A  
Rat...

## REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send ABB / 2CCS861001R0085 with the required quantity to [info@electricaonline.com](mailto:info@electricaonline.com) or use [electricaonline.com/request-quote](https://electricaonline.com/request-quote).

### GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.