

INDUSTRIAL COMPONENT DATA

2CCS813001R0401 ABB S803B-D40 High Performance Circuit Breaker

Brand: ABB | Manufacturer Part Number: 2CCS813001R0401



Manufacturer	ABB
MPN / Reference	2CCS813001R0401
Catalog number	813001
Category	Miniature circuit breaker (MCB)
Minimum order	1 Pcs
Document ID	EO-E17D8B8E9B
Generated	2026-08-03

Product Overview

S803B-D40 High Performance Circuit Breaker

Int.aut. S803B-D40 3p 40A D 16kA

S803B-D40 High Performance MCB

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path **ABB > Industrial > S800C**

Additional Product Information

ABB EcoSolutions

ABB EcoSolutions Yes

EcoSolutions Profile 9AKK108471A1082

Recyclability Rate of the Product acc. to EN45555 Design for Closing Resource Loops - Standard EN45555 - 86.29 %

ABB Site Meeting Group Waste To Landfill Target No non-hazardous waste is sent to a landfill

End Of Life Disassembling Instructions 9AKK108470A2575

Environmental Product Declaration - EPD 9AKK108470A1695

9AKK108470A1696

Technical

Rated Ultimate Short-Circuit Breaking Capacity (Icu) (400 V AC) 16 kA
(225 V DC) 10 kA

Rated Service Short-Circuit Breaking Capacity (Ics) (400 V AC) 10 kA
(225 V DC) 10 kA

Contact Position Indication ON / OFF / TRIP
Energy Limiting Class 3
Number of Protected Poles 3
Number of Poles 3P
Tightening Torque 3.5 N·m
Release Type D
Actuator Marking I / O
Recommended Screw Driver Pozidriv 2
Accessories Available Yes
Remarks Connection from top and bottom
Connecting with CU only
IP40 in enclosure with cover
Cage terminal with captive screw
Connecting Capacity Flexible 0 ... 50 mm²
Rigid 0 ... 70 mm²
Terminal Type Screw Terminals
Electrical
Tripping Characteristic D
Rated Operational Voltage acc. to IEC 60898-1 400 V AC
acc. to IEC 60947-2 400 V AC
Rated Insulation Voltage (Ui) acc. to IEC/EN 60664-1 500 V
Rated Impulse Withstand Voltage (Uimp) 6 kV
Input Voltage Type AC/DC
Rated Current (In) 40 A
Rated Short-Circuit Capacity (400 V AC) 10 kA
Frequency (f) 50...60 Hz
Rated Frequency (f) 50/60 Hz
Power Loss 11.1 W
at Rated Operating Conditions per Pole 3.7 W
Overvoltage Catego...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send ABB / 2CCS813001R0401 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.