

INDUSTRIAL COMPONENT DATA

1SFA619201R3026 ABB SELECTOR SWITCH C2SS2-30B-20

Brand: ABB | Manufacturer Part Number: 1SFA619201R3026



Manufacturer	ABB
MPN / Reference	1SFA619201R3026
Catalog number	619201
Category	Selector switch, complete
Minimum order	1 Pcs
Document ID	EO-FBE7CE2CC5
Generated	2026-07-29

Product Overview

SELECTOR SWITCH#C2SS2-30B-20
 SELECTOR with metal ring
 C2SS2-30B-20 Selector Switch

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path ABB > Command and signaling > elements PDA

Additional Product Information

Ordering

Minimum Order Quantity 10 piece
 Customs Tariff Number 8536501999

Popular Downloads

Data Sheet, Technical Information 1SFC151007C02__
 Instructions and Manuals 1SFC151011M0201

Dimensions

Product Net Width 0.03 m
 Product Net Height 0.03 m
 Product Net Depth / Length 0.072 m
 Product Net Weight 0.032 kg

Technical

Ambient Air Temperature Operation -25 ... +70 °C
 Storage -40 ... +85 °C

Color Black
Actuator Type Short handle
Bezel Material Metal
Illumination Non-illuminated
Function Maintained
Sub-Function 2-position
Maintained Positions A, C
Number of Auxiliary Contacts NC 0
Number of Auxiliary Contacts NO 2
Enclosure Type NEMA Type1
Type12
Type13
Type3R
Type4
Type4X
Pollution Degree 3
Rated Insulation Voltage (Ui) 300 V
Rated Impulse Withstand Voltage (Uimp) 6 kV
Rated Frequency (f) 50 / 60 Hz
Rated Operational Voltage 24 ... 300 V
Maximum 300 V
Rated Operational Current DC-13 (Ie) (24 V) 0.3 A
(125 V) 0.2 A
Rated Operational Current AC-15 (Ie) (240 V) 2 A
(220 / 240 V) 2 A
Power Loss Maximum 5 W
Mechanical Durability 0.5 million
Connecting Capacity Flexible with Ferrule 1 x 0.5...1.5 mm²
Flexible with Ferrule 2 x 0.5...1.5 mm²
Flexible with Insulated Ferrule 1 x 0.5...1.5 mm²
Flexible with Insulated Ferrule 2 x 0.5...1.5 mm²
Flexible 1 x 0.5 ...1.5 mm²
Flexible 2 x 0.5 ...1.5 mm²
Solid 1 x 0.5...1.5 mm²
Solid 2 x 0.5...1.5 mm²
Terminal Type Screw Terminals
Tightening Torque 0.8 N·m
Wire Stripping Length 6 mm
Technical UL/CSA
Connecting Capacity UL/CSA 1x 22...14 AWG
2x 22...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send ABB / 1SFA619201R3026 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.