

**INDUSTRIAL COMPONENT DATA**

# 1SFA619210R1071 ABB SELECTOR SWITCH C3SS1-10R-11

Brand: ABB | Manufacturer Part Number: 1SFA619210R1071



|                 |                           |
|-----------------|---------------------------|
| Manufacturer    | ABB                       |
| MPN / Reference | 1SFA619210R1071           |
| Catalog number  | 619210                    |
| Category        | Selector switch, complete |
| Minimum order   | 1 Pcs                     |
| Document ID     | EO-49EB1FFD41             |
| Generated       | 2026-08-02                |

## Product Overview

SELECTOR SWITCH#C3SS1-10R-11  
SELEC.3 POS. MAN. ABC,1NA+1NC, R  
C3SS1-10R-11 Selector Switch

**STRUCTURED PRODUCT DATA**

## Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

## Classification & Catalog Path

|              |                                            |
|--------------|--------------------------------------------|
| Catalog path | ABB > Command and signaling > elements PDA |
|--------------|--------------------------------------------|

## Additional Product Information

**Ordering**

Minimum Order Quantity 10 piece

Customs Tariff Number 8536501999

**Popular Downloads**

Data Sheet, Technical Information 1SFC151007C02\_\_

Instructions and Manuals 1SFC151011M0201

**Dimensions**

Product Net Width 0.03 m

Product Net Height 0.03 m

Product Net Depth / Length 0.072 m

Product Net Weight 0.024 kg

**Technical**

Ambient Air Temperature Operation -25 ... +70 °C

Storage -40 ... +85 °C

Color Red  
Actuator Type Short handle  
Bezel Material Plastic  
Illumination Non-illuminated  
Function Maintained  
Sub-Function 3-position  
Maintained Positions A, B, C  
Number of Auxiliary Contacts NC 1  
Number of Auxiliary Contacts NO 1  
Enclosure Type NEMA Type1  
Type12  
Type13  
Type3R  
Type4  
Type4X  
Rated Insulation Voltage (Ui) 300 V  
Rated Impulse Withstand Voltage (Uimp) 6 kV  
Rated Frequency (f) 50 / 60 Hz  
Rated Operational Voltage Maximum 300 V  
Rated Operational Current DC-13 (Ie) (24 V) 0.3 A  
(125 V) 0.2 A  
Rated Operational Current AC-15 (Ie) (240 V) 2 A  
(220 / 240 V) 2 A  
Power Loss Maximum 5 W  
Mechanical Durability 0.5 million  
Connecting Capacity Flexible with Ferrule 1 x 0.5...1.5 mm<sup>2</sup>  
Flexible with Ferrule 2 x 0.5...1.5 mm<sup>2</sup>  
Flexible with Insulated Ferrule 1 x 0.5...1.5 mm<sup>2</sup>  
Flexible with Insulated Ferrule 2 x 0.5...1.5 mm<sup>2</sup>  
Flexible 1 x 0.5 ...1.5 mm<sup>2</sup>  
Flexible 2 x 0.5 ...1.5 mm<sup>2</sup>  
Solid 1 x 0.5...1.5 mm<sup>2</sup>  
Solid 2 x 0.5...1.5 mm<sup>2</sup>  
Terminal Type Screw Terminals  
Tightening Torque 0.8 N·m  
Wire Stripping Length 6 mm  
Technical UL/CSA  
Connecting Capacity UL/CSA 1x 22...14 AWG  
2x 22...14 AWG  
Environmental  
Degre...

## REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send ABB / 1SFA619210R1071 with the required quantity to [info@electricaonline.com](mailto:info@electricaonline.com) or use [electricaonline.com/request-quote](https://electricaonline.com/request-quote).

### GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.