

INDUSTRIAL COMPONENT DATA

1SAZ711201R1047 ABB T16-16 Thermal Overload Relay

Brand: ABB | Manufacturer Part Number: 1SAZ711201R1047



Manufacturer	ABB
MPN / Reference	1SAZ711201R1047
Catalog number	711201
Category	Thermal overload relay
Minimum order	1 Pcs
Document ID	EO-A3E3B0D788
Generated	2026-08-01

Product Overview

T16-16 Thermal Overload Relay
T16-16 RELe TeRM CLASS 10, 13.0-16.0 A
T16-16 Thermal Overload Relay 13 ... 16 A

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path ABB > Contactors and overload relays > Thermal Relays

Additional Product Information

Ordering

Minimum Order Quantity 1 piece
Customs Tariff Number 85364900

Popular Downloads

Data Sheet, Technical Information 2CDC106020D0201
Instructions and Manuals 2CDC106019M6802
Instructions and Manuals (Part 2) 1SAC200017M0002
Time-Current Characteristic Curve 1SAZ700505F0018
CAD Dimensional Drawing 2CDC001079B0201
Dimension Diagram 1SAZ700404F0001
Dimensions
Product Net Width 45 mm
Product Net Height 76.7 mm
Product Net Depth / Length 53.5 mm

Product Net Weight 0.104 kg

Technical

Setting Range 13 ... 16 A

Rated Operational Voltage Auxiliary Circuit 600 V AC/DC

Main Circuit 690 V AC

Rated Operational Current (I_e) 16 A

Rated Frequency (f) Auxiliary Circuit 50 Hz

Auxiliary Circuit 60 Hz

Auxiliary Circuit DC

Main Circuit 50 Hz

Main Circuit 60 Hz

Rated Impulse Withstand Voltage (U_{imp}) Auxiliary Circuit 6 kV

Main Circuit 6 kV

Rated Insulation Voltage (U_i) 690 V

Number of Poles 3P

Number of Auxiliary Contacts NC 1

Number of Auxiliary Contacts NO 1

Number of Protected Poles 3

Conventional Free-air Thermal Current (I_{th}) Auxiliary Circuit NC 6 A

Auxiliary Circuit NO 4 A

Rated Operational Current AC-15 (I_e) (120 V) NC 3 A

(120 V) NO 0.5 A

(240 V) NC 3 A

(240 V) NO 0.5 A

(400 V) NC 0.75 A

(400 V) NO 0.5 A

(500 V) NC 0.75 A

(500 V) NO 0.5 A

Rated Operational Current DC-13 (I_e) (125 V) NC 0.55 A

(125 V) NO 0.55 A

(24 V) NC 1.25 A

(24 V) NO 1.25 A

(250 V) NC 0.27 A

(250 V) NO 0.27 A

(500 V) NC 0.15 A

(500 V) NO 0.15 A

(60 V) NC 0.55 A

(60 V) NO 0.55 A

Degree of Protection IP20

Pollutio...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send ABB / 1SAZ711201R1047 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.