

INDUSTRIAL COMPONENT DATA

T4D320 1SDA054597R1 ABB T4D 320 3p F F

Brand: ABB | Manufacturer Part Number: T4D320



Manufacturer	ABB
MPN / Reference	T4D320
Catalog number	1SDA054597R1
Category	Power circuit-breaker for trafo/generator/installation protection
Minimum order	1 Pcs
Document ID	EO-BC04752A84
Generated	2026-08-04

Product Overview

T4D 320 3p F F

T4D320 3P F F

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path ABB > Molded case "Isomax-Tmax" > T4

Additional Product Information

Material Compliance

REACH Declaration 9AKK108466A1425

RoHS Declaration 9AKK108466A1424

RoHS Information Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019

Conflict Minerals Reporting Template (CMRT) Document availability on demand

Toxic Substances Control Act - TSCA 9AKK108467A8326

SCIP 715f0fe9-038a-41b1-bd92-20167499bc69 Italy

Environmental

Environmental Information 9AKK10103A1057

Ordering

E-Number (Finland) 3655611

EAN 8015644556952

Minimum Order Quantity 1 piece

Customs Tariff Number 85362090

Dimensions

Product Net Width 105 mm
Product Net Height 205 mm
Product Net Depth / Length 103.5 mm
Product Net Weight 3.254 kg
Container Information
Package Level 1 Units 1 piece
Package Level 1 Width 248 mm
Package Level 1 Height 240 mm
Package Level 1 Depth / Length 285 mm
Package Level 1 Gross Weight 2.5 kg
Package Level 1 EAN 8015644556952
Additional Information
Product Main Type SACE Tmax T
Product Name Moulded Case Circuit Breaker
Product Type Switch Disconnecter
Suitable For T4
Suitable for Product Class Moulded Case Circuit Breakers
Version F
Technical
Mechanical Durability 20000 cycle
120 cycles per hour
Number of Poles 3P
Power Loss at Rated Operating Conditions per Pole 17.6 W
Rated Impulse Withstand Voltage (Uimp) 8 kV
Rated Insulation Voltage (Ui) 1000 V
Rated Operational Voltage 690 V AC
750 V DC
Rated Short-time Withstand Current Low Voltage (Icw) for 1 s 3.6 A
Rated Uninterrupted Current (Iu) 320 A
Short-Circuit Performance Level D
Standards IEC
Su...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send ABB / T4D320 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.