

INDUSTRIAL COMPONENT DATA

T4N320 1SDA054117R1 ABB T4N 320 PR221DS-LS/I In 320 3p F F

Brand: ABB | Manufacturer Part Number: T4N320



Manufacturer	ABB
MPN / Reference	T4N320
Catalog number	1SDA054117R1
Category	Power circuit-breaker for trafo/generator/installation protection
Minimum order	1 Pcs
Document ID	EO-2F16F60E3B
Generated	2026-08-06

Product Overview

T4N 320 PR221DS-LS/I In=320 3p F F

T4N320 PR221DS LS/I R320 3P F F

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path ABB > Molded case "Isomax-Tmax" > T4

Additional Product Information

Material Compliance

REACH Declaration 9AKK108466A1425

RoHS Declaration 9AKK108466A1424

RoHS Information Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019

Conflict Minerals Reporting Template (CMRT) Document availability on demand

Toxic Substances Control Act - TSCA 9AKK108467A8326

SCIP c8261068-2394-4e97-b79c-4aa8dfdf22fd Italy

Environmental

Environmental Information 9AKK10103A1057

Ordering

E-Number (Finland) 3655174

E-Number (Sweden) 3180305

EAN 8015644552169

Minimum Order Quantity 1 piece

Customs Tariff Number 85362090

Dimensions

Product Net Width 105 mm

Product Net Height 205 mm

Product Net Depth / Length 103.5 mm

Product Net Weight 3.639 kg

Container Information

Package Level 1 Units 1 piece

Package Level 1 Width 250 mm

Package Level 1 Height 246 mm

Package Level 1 Depth / Length 290 mm

Package Level 1 Gross Weight 3.83 kg

Package Level 1 EAN 8015644552169

Additional Information

Product Main Type SACE Tmax T

Product Name Moulded Case Circuit Breaker

Product Type Automatic Circuit Breaker

Suitable For T4

Suitable for Product Class Moulded Case Circuit Breakers

Version F

Technical

Electrical Durability 6000 cycle

120 cycles per hour

Gross Volume 17,835 cm³

Mechanical Durability 20000 cycle

240 cycles per hour

Number of Poles 3P

Power Loss at Rated Operating Conditions per Pole 17.6 W

Rated Current (In) 320 A

Rated Impulse Withstand Voltage (Uimp) 8 kV

Rated Insulation Voltage (Ui) 1000 V

Rated Operational Voltage 690 V AC

Rated Service Short-Circuit Br...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send ABB / T4N320 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.