

INDUSTRIAL COMPONENT DATA

T5L400 1SDA054556R1 ABB T5L 400 Ekip M-LRIU In 400 3p F F

Brand: ABB | Manufacturer Part Number: T5L400



Manufacturer	ABB
MPN / Reference	T5L400
Catalog number	1SDA054556R1
Category	Power circuit-breaker for trafo/generator/installation protection
Minimum order	1 Pcs
Document ID	EO-AACE278AF6
Generated	2026-08-06

Product Overview

T5L 400 Ekip M-LRIU In=400 3p F F

T5L400 Ekip M-LRIU R400 3P F F

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	ABB > Molded case "Isomax-Tmax" > T5
--------------	--------------------------------------

Additional Product Information

C.BREAKER TMAX T5L 400 FIXED THREE-POLE WITH FRONT TERMINALS AND SOLID-STATE RELEASE IN AC Ekip M-LRIU R 400

Ordering

EAN:8015644556570

Minimum Order Quantity:1 piece

Customs Tariff Number:85362090

Dimensions

Product Net Width:140mm

Product Net Height:205mm

Product Net Depth:103.5mm

Product Net Weight:5.1kg

Container Information

Package Level 1 Units:1 piece

Package Level 1 Width:248 mm

Package Level 1 Height:240 mm

Package Level 1 Length:285 mm

Package Level 1 Gross Weight:5.1 kg

Package Level 1 EAN:8015644556570

Environmental

RoHS Status:Planned to follow EU Directive 2002/95/EC August 18, 2005 and amendment after 2007 Q2

Additional Information

Electrical Durability:7000 cycle

60 cycles per hour

IIT Publishing Status:Level 0 - Information enabled

Mechanical Durability:20000 cycle

120 cycles per hour

Number of Poles:3

Power Loss:at Rated Operating Conditions per Pole 16,5 W

Product Main Type:SACE Tmax T

Product Name:Automatic Circuit Breaker

Product Type:CB

Rated Current (In):400 A

Rated Impulse Withstand Voltage (Uimp):8 kV

Rated Insulation Voltage (Ui):1000 V

Rated Operational Voltage:690 V AC

750 V DC

Rated Service Short-Circuit Breaking Capacity (Ics):(220 V AC) 200 kA

(230 V AC) 200 kA

(380 V AC) 120 kA

(400 V AC) 120 kA

(415 V AC) 120 kA

(440 V AC) 100 kA

(500 V AC) 85 kA

(690 V AC) 70 kA

Rated Short-time Withstand Current (Icw):for 1 s 5 A

Rated Ultimate Short-Circuit Breaking Capacity (Icu):(220 V AC) 20 kA

(230 V AC) 20 kA

(380 V AC) 120 kA

(400 V AC) 120 kA

(415 V...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEW

Send ABB / T5L400 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.

GLOBAL OFFICES

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.