

INDUSTRIAL COMPONENT DATA

1SDA060452R1 ABB T5N400 PR221DS-LSI R400 4P F F UL

Brand: ABB | Manufacturer Part Number: 1SDA060452R1



Manufacturer	ABB
MPN / Reference	1SDA060452R1
Catalog number	060452
Category	Power circuit-breaker for trafo/generator/installation protection
Minimum order	1 Pcs
Document ID	EO-5E88E0577B
Generated	2026-08-05

Product Overview

T5N400 PR221DS-LSI R400 4P F F UL
T5N 400 UL/CSA PR222DS/P-LSI 400 4p F F

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	ABB > Molded case "Isomax-Tmax"
--------------	---------------------------------

Additional Product Information

ABB EcoSolutions
Material Compliance
REACH Declaration 9AKK108466A1425
RoHS Declaration 9AKK108466A1424
RoHS Information Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019
Conflict Minerals Reporting Template (CMRT) 9AKK108467A5658
Toxic Substances Control Act - TSCA 9AKK108467A8326
Environmental
Environmental Information 9AKK10103A1056
9AKK108467A6707
Ordering
Order Code US and Canada T5N400CW-4
EAN 8015644629403
Minimum Order Quantity 1 piece
Customs Tariff Number 85362090

Dimensions

Product Net Width 186 mm

Product Net Height 205 mm

Product Net Depth / Length 103.5 mm

Product Net Weight 6.2 kg

Container Information

Package Level 1 EAN 8015644629403

Additional Information

Product Main Type SACE Tmax T

Product Name Moulded Case Circuit Breaker

Product Type Automatic Circuit Breaker

Suitable For T5

Suitable for Product Class Moulded Case Circuit Breakers

Version F

Technical

Mechanical Durability 20000 cycle

120 cycles per hour

Number of Poles 4P

Power Loss at Rated Operating Conditions per Pole 16.5 W

Rated Current (In) 400 A

Rated Impulse Withstand Voltage (Uimp) 8 kV

Rated Insulation Voltage (Ui) 1000 V

Rated Operational Voltage 600 V AC

Rated Uninterrupted Current (Iu) 400 A

Release PR222DS/P-LSI

Release Type EL

Short-Circuit Performance Level N

Standards UL

Sub-type T5

Terminal Connection Type Fixed Circuit-Breakers

Front

Test Voltage Max (Utest) 3500 V

Technical UL/CSA

Interrupting Rating acc. to UL489 (240 V AC) 65 kA

(480 V AC) 25 kA

(600 V AC) 18....

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEWSend ABB / 1SDA060452R1 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.**GLOBAL OFFICES**

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.