

INDUSTRIAL COMPONENT DATA

1SDA061694R1 ABB T6H800 PR221DS LS/I R800 3P F F UL

Brand: ABB | Manufacturer Part Number: 1SDA061694R1



Manufacturer	ABB
MPN / Reference	1SDA061694R1
Catalog number	061694
Category	Power circuit-breaker for trafo/generator/installation protection
Minimum order	1 Pcs
Document ID	EO-C9B9E81C6C
Generated	2026-08-06

Product Overview

T6H800 PR221DS LS/I R800 3P F F UL
T6H 800 UL/CSA PR221DS-LS/I 800 3p F F

STRUCTURED PRODUCT DATA

Technical Specifications

No structured technical attributes are currently available. Submit an RFQ for technical review.

Classification & Catalog Path

Catalog path	ABB > Molded case "Isomax-Tmax"
--------------	---------------------------------

Additional Product Information

ABB EcoSolutions
Material Compliance
REACH Declaration 9AKK108466A1425
RoHS Declaration 9AKK108466A1424
RoHS Information Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019
Conflict Minerals Reporting Template (CMRT) 9AKK108467A5658
Toxic Substances Control Act - TSCA 9AKK108467A8326
Environmental
Environmental Information 9AKK10103A1058
9AKK108467A6707
Ordering
Order Code US and Canada T6H800BW
EAN 8015644642334
Minimum Order Quantity 1 piece
Customs Tariff Number 85362090

Dimensions

Product Net Width 210 mm

Product Net Height 268 mm

Product Net Depth / Length 103.5 mm

Product Net Weight 9.5 kg

Container Information

Package Level 1 Units box 1 piece

Package Level 1 Width 321 mm

Package Level 1 Height 288 mm

Package Level 1 Depth / Length 321 mm

Package Level 1 Gross Weight 11 kg

Package Level 1 EAN 8015644642334

Additional Information

Product Main Type SACE Tmax T

Product Name Moulded Case Circuit Breaker

Product Type Automatic Circuit Breaker

Suitable For T6

Suitable for Product Class Moulded Case Circuit Breakers

Version F**Technical**

Mechanical Durability 20000 cycle

120 cycles per hour

Number of Poles 3P

Power Loss at Rated Operating Conditions per Pole 32 W

Rated Current (In) 800 A

Rated Impulse Withstand Voltage (Uimp) 8 kV

Rated Insulation Voltage (Ui) 1000 V

Rated Operational Voltage 600 V AC

Rated Uninterrupted Current (Iu) 800 A

Release PR221DS-LS/I

Release Type EL

Short-Circuit Performance Level H

Standards UL

Sub-type T6

Terminal Connection Type...

REQUEST PRICE, AVAILABILITY & TECHNICAL REVIEWSend ABB / 1SDA061694R1 with the required quantity to info@electricaonline.com or use electricaonline.com/request-quote.**GLOBAL OFFICES**

Germany: Lise-Meitner-Straße 13, 89081 Ulm | USA: 16225 Park Ten Pl #500, Houston, TX 77084 | UAE: HDS Business Centre Tower, Cluster M, 33rd Floor, JLT, Dubai

Catalog-generated document. Product names, marks and specifications belong to their respective owners. Verify safety-critical, compatibility and certification requirements against the manufacturer documentation before purchase or installation.